

DIN EN 14025:2024-02 (E)

Tanks for the transport of dangerous goods - Metallic pressure tanks - Design and construction

Contents

Page

European foreword	5
1 Scope	7
2 Normative references	7
3 Terms, definitions and symbols	8
3.1 Terms and definitions	8
3.2 Symbols	9
4 Materials	10
4.1 General	10
4.2 Compatibility	11
5 Design	11
5.1 General	11
5.2 Minimum shell thickness	11
5.3 Reduction of shell thickness	12
5.4 Protection of the shell	12
5.5 Protection of equipment	13
5.6 Other design requirements	13
6 Calculation	14
6.1 General	14
6.1.1 General	14
6.1.2 Calculation scheme for the wall thickness of metallic pressure tanks of RID/ADR Chapter 6.8	14
Figure 1 -- Calculation scheme for the wall thickness of metallic pressure tanks of Chapter 6.8 of RID/ADR	15
6.1.3 Calculation scheme for the wall thickness of metallic portable pressure tanks of RID/ADR Chapter 6.7	15
Figure 2 -- Calculation scheme for the wall thickness of metallic portable pressure tanks of Chapter 6.7 of RID/ADR	16
6.2 Design criteria	17
Table 1 -- Design criteria for Chapter 6.8 tanks	17
Table 2 -- Design criteria for Chapter 6.7 tanks	18
6.3 Calculation for internal pressure	18
6.3.1 General	18
6.3.2 Wall thickness of the cylindrical section	18
6.3.3 Wall thickness of ends	18
Figure 3 -- Geometry of ends	19
Figure 4 -- Position of welds in ends	20
Table 3 -- Procedure for calculation of weakening factor k for openings in the knuckle region (design)	22

6.3.4	Wall thickness of conical sections	22
Figure 5 --	Junction between cylinder and cone; angle	23
Figure 6 --	Geometry of cone/cylinder intersection; small end	24
6.3.5	Openings and reinforcements	25
Figure 7 --	Wall thickness ratio for branches	25
Figure 8 --	Shells with isolated openings; examples for reinforcement	29
6.3.6	Manhole covers	32
Figure 9 --	Circular or elliptical flat cover with narrow faced gasket	33
Figure 10 --	Circular or elliptical flat cover with full faced gasket (for liquid only)	33
Figure 11 --	Coefficient Z for elliptical ends	34
Figure 12 --	Spherically domed and bolted cover with narrow faced gasket	36
6.3.7	Flanges, joints, bolts	37
Table 4 --	Gasket materials and contact facings: gasket factors m for operating conditions and minimum design seating stress y	37
6.4	Calculation for external pressure	39
6.4.1	General	39
6.4.2	Tanks, where external over pressure is part of operating conditions	39
6.4.3	Tanks, where external over pressure is not part of operating conditions	39
6.4.4	Test	39
6.5	Tank to frame connection/interface and other attachments	39
7	Construction and manufacturing	40
7.1	General requirements	40
7.2	Cutting	40
7.3	Forming	41
7.3.1	General	41
7.3.2	Cold forming	41
7.3.3	Hot forming	41
7.3.4	Ends	42
7.3.5	Heat treatment and normalizing	42
7.4	Welding	42
7.4.1	Qualification	42
7.4.2	Welded joints	42
7.4.3	Examination and testing of welds	43
7.4.4	Temporary attachments	43
7.5	Manufacturing tolerances	43
7.5.1	Plate alignment	43
Figure 13 --	Seams which do require a taper	44
7.5.2	Defects of form	44
7.5.3	Thickness	44
7.5.4	Dished ends	44
7.5.5	Cylindrical sections	44
8	Repairs	45
8.1	General	45
8.2	Repair of surface defects in the parent metal	45
8.3	Repair of weld defects	45
Annex A (informative)	Sample calculation for tank containers according to RID/ADR Chapter 6.8 ...	46
A.1	Introduction	46
A.2	Dimensions, characteristics of materials, operating and testing conditions	46

Figure A.1 -- Sample tank, overview	47
A.3 Calculation according to branch A	47
A.4 Calculation according to branch B	47
A.5 Calculation according to branch C	48
A.6 Calculation according to branch D	50
Figure A.2 -- Example for a manhole opening 500 mm × 150 mm with neckring 200 mm × 5 mm as reinforcement	60
A.7 Results	60
Table A.1 -- Results of sample calculation (wall thickness e in mm; X not applicable)	61
Annex B (informative) Explosion pressure shock resistant design of tanks	62
Bibliography	64