

# DIN EN 13616-2:2025-12 (E)

## Overfill prevention devices for static tanks for liquid fuels - Part 2: Overfill prevention devices without a closure device (includes Amendment A1:2025)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>4</b>
<b>4</b>	<b>Requirements .....</b>	<b>6</b>
<b>4.1</b>	<b>Effectiveness .....</b>	<b>6</b>
<b>4.1.1</b>	<b>Signal equal or greater than level L1 .....</b>	<b>6</b>
<b>4.1.2</b>	<b>Signal below level L1 .....</b>	<b>6</b>
<b>4.1.3</b>	<b>Functional requirements .....</b>	<b>6</b>
<b>4.2</b>	<b>Durability .....</b>	<b>12</b>
<b>4.2.1</b>	<b>Durability at ambient temperature, Tamb .....</b>	<b>12</b>
<b>4.2.2</b>	<b>Durability against chemical attack .....</b>	<b>12</b>
<b>4.2.3</b>	<b>Durability against operational cycles .....</b>	<b>12</b>
<b>4.3</b>	<b>Electro-magnetic compatibility (EMC) .....</b>	<b>12</b>
<b>4.4</b>	<b>Fail safe .....</b>	<b>12</b>
<b>5</b>	<b>Testing .....</b>	<b>12</b>
<b>5.1</b>	<b>Effectiveness .....</b>	<b>12</b>
<b>5.1.1</b>	<b>Signal equal or greater than level L1 .....</b>	<b>12</b>
<b>5.1.2</b>	<b>Signal below level L1 .....</b>	<b>12</b>
<b>5.1.3</b>	<b>Functional requirements .....</b>	<b>13</b>
<b>5.2</b>	<b>Durability .....</b>	<b>15</b>
<b>5.2.1</b>	<b>Durability at ambient temperature, Tamb .....</b>	<b>15</b>
<b>5.2.2</b>	<b>Durability against chemical attack .....</b>	<b>15</b>
<b>5.2.3</b>	<b>Durability against operational cycles .....</b>	<b>16</b>
<b>5.3</b>	<b>EMC test .....</b>	<b>16</b>
<b>5.4</b>	<b>Fail safe .....</b>	<b>17</b>
<b>6</b>	<b>Assessment and verification of constancy of performance -- AVCP .....</b>	<b>17</b>
<b>6.1</b>	<b>General .....</b>	<b>17</b>
<b>6.2</b>	<b>Type testing .....</b>	<b>17</b>
<b>6.2.1</b>	<b>General .....</b>	<b>17</b>
<b>6.2.2</b>	<b>Test samples, testing and compliance criteria .....</b>	<b>18</b>
<b>6.2.3</b>	<b>Test reports .....</b>	<b>18</b>
<b>6.2.4</b>	<b>Shared other party results .....</b>	<b>19</b>
<b>6.2.5</b>	<b>Cascading determination of the product type results .....</b>	<b>19</b>
<b>6.3</b>	<b>Factory production control (FPC) .....</b>	<b>20</b>
<b>6.3.1</b>	<b>General .....</b>	<b>20</b>
<b>6.3.2</b>	<b>Requirements .....</b>	<b>21</b>
<b>6.3.3</b>	<b>Product specific requirements .....</b>	<b>23</b>
<b>6.3.4</b>	<b>Procedure for modifications .....</b>	<b>24</b>
<b>6.3.5</b>	<b>One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity .....</b>	<b>24</b>
<b>7</b>	<b>Marking, labelling and packaging .....</b>	<b>25</b>
<b>Annex A (informative) Setting of the overfill prevention sensor .....</b>		<b>26</b>
<b>Bibliography .....</b>		<b>30</b>