DIN EN 14620-2:2006-12 (E)

Design and manufacture of site built, ver tical, cylindrical, flat-bottomed steel tanks for the storage of refrigerated, liquefied gases with operating temperatures between 0 °C and -165 °C - Part 2: Metallic components

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 7

4 Materials 8
4.1 General 8
4.2 Temperatures 8
4.3 Primary and secondary liquid container 8
4.4 Vapour container/outer tank 11
4.5 Other components 12

5 Design 13
5.1 Design theory 13
5.2 Primary and secondary liquid container 16
5.3 Vapour container (outer tank) 29
5.4 Suspended roof 33
5.5 Nozzles 33
5.6 Primary and secondary containment, bottom connections 36
5.7 Connections between containers 36
5.8 Other details 36

6 Fabrication 38
6.1 Handling of materials 38
6.2 Plate preparation and tolerances 38
6.3 Tolerances 39
6.4 Roof 42
6.5 Temporary attachments 42

7 Welding procedures 42
7.1 General 42
7.2 WPAR requirements 43
7.3 Impact testing 43
7.4 9 % Nickel steel 43
7.5 Welders and welding operators 44
7.6 Production test plates 44

8 Welding 45
8.1 Tack and temporary welds 45
8.2 Atmospheric conditions 45
8.3 Preheating 45
8.4 Post-weld heat treatment 45

9 Inspection 47
9.1 Qualification of NDE personnel 47
9.2 Inspection procedures 47

9.3 Type of inspections 47
9.4 Visual inspection 51
9.5 Dye penetrant examination 51
9.6 Magnetic particle examination 51
9.7 Vacuum box examination 51
9.8 Ammonia tightness test 52
9.9 Soap bubble examination 52
9.10 Radiographic examination 52
9.11 Ultrasonic examination 53
9.12 Acceptance criteria 53
9.13 Unacceptable defects in horizontal welds 53
9.14 Acceptable thinning after grinding 54

Annex A (informative) Actions on membrane 55

Annex B (informative) Determination of the load and fatigue curves for membrane 56

Bibliography 57

Figures Figure 1 -- Typical bottom layout 18

Figure 2 -- Design flowchart for membranes 23

Figure 3 -- Typical shell-roof compression areas 32

Figure 4 -- Typical roof nozzle with thermal distance piece 35

Figure 5 -- Outward and inward peaking 41

Figure 6 -- Gauge for measuring peaking 41

Figure B.1 -- Flowchart for membranes 56

Tables Table 1 -- Product and steel class 9

Table 2 -- Minimum Charpy V-notch impact test energy 11

Table 3 -- Steel for vapour container/outer tank 12

Table 4 -- Determination of the maximum allowable design stress 14

Table 5 -- Partial load and material factors for types I, II, III and IV steel 16

Table 6 -- Minimum shell plate thickness 20

Table 7 -- k factors for S-N curves (normal distribution assumed) 28

Table 8 -- Minimum size of top corner ring 33

Table 9 -- Radius tolerances 39

Table 10 -- Maximum differences between the design and the as built profile 40

Table 11 -- Tolerance limits on local deformation in welds 40

Table 12 -- Misalignment at vertical joints 42

Table 13 -- Holding times at lower temperatures 46

Table 14 -- Weld inspections of primary and secondary liquid container 48

Table 15 -- Extent of radiographic/ultrasonic examination of shell welds of primary and secondary liquid container 48

Table 16 -- Inspection of vapour barrier/liner 50

Table 17 -- Extent of radiographic and ultrasonic examination of shell plate welds of vapour containers 51

Table A.1 -- Static action 55

Table A.2 -- Cyclic action 55

Table A.3 -- Accidental action 55