

DIN EN 14620-2:2006-12 (E)

Design and manufacture of site built, vertical, cylindrical, flat-bottomed steel tanks for the storage of refrigerated, liquefied gases with operating temperatures between 0 °C and -165 °C - Part 2: Metallic components

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	7
4	Materials	8
4.1	General	8
4.2	Temperatures	8
4.3	Primary and secondary liquid container	8
4.4	Vapour container/outer tank	11
4.5	Other components	12
5	Design	13
5.1	Design theory	13
5.2	Primary and secondary liquid container	16
5.3	Vapour container (outer tank)	29
5.4	Suspended roof	33
5.5	Nozzles	33
5.6	Primary and secondary containment, bottom connections	36
5.7	Connections between containers	36
5.8	Other details	36
6	Fabrication	38
6.1	Handling of materials	38
6.2	Plate preparation and tolerances	38
6.3	Tolerances	39
6.4	Roof	42
6.5	Temporary attachments	42
7	Welding procedures	42
7.1	General	42
7.2	WPAR requirements	43
7.3	Impact testing	43
7.4	9 % Nickel steel	43
7.5	Welders and welding operators	44
7.6	Production test plates	44
8	Welding	45
8.1	Tack and temporary welds	45
8.2	Atmospheric conditions	45
8.3	Preheating	45
8.4	Post-weld heat treatment	45
9	Inspection	47
9.1	Qualification of NDE personnel	47
9.2	Inspection procedures	47

9.3	Type of inspections	47
9.4	Visual inspection	51
9.5	Dye penetrant examination	51
9.6	Magnetic particle examination	51
9.7	Vacuum box examination	51
9.8	Ammonia tightness test	52
9.9	Soap bubble examination	52
9.10	Radiographic examination	52
9.11	Ultrasonic examination	53
9.12	Acceptance criteria	53
9.13	Unacceptable defects in horizontal welds	53
9.14	Acceptable thinning after grinding	54
Annex A (informative) Actions on membrane		55
Annex B (informative) Determination of the load and fatigue curves for membrane		56
Bibliography		57
Figures Figure 1 -- Typical bottom layout		18
Figure 2 -- Design flowchart for membranes		23
Figure 3 -- Typical shell-roof compression areas		32
Figure 4 -- Typical roof nozzle with thermal distance piece		35
Figure 5 -- Outward and inward peaking		41
Figure 6 -- Gauge for measuring peaking		41
Figure B.1 -- Flowchart for membranes		56
Tables Table 1 -- Product and steel class		9
Table 2 -- Minimum Charpy V-notch impact test energy		11
Table 3 -- Steel for vapour container/outer tank		12
Table 4 -- Determination of the maximum allowable design stress		14
Table 5 -- Partial load and material factors for types I, II, III and IV steel		16
Table 6 -- Minimum shell plate thickness		20
Table 7 -- k factors for S-N curves (normal distribution assumed)		28
Table 8 -- Minimum size of top corner ring		33
Table 9 -- Radius tolerances		39
Table 10 -- Maximum differences between the design and the as built profile		40
Table 11 -- Tolerance limits on local deformation in welds		40
Table 12 -- Misalignment at vertical joints		42
Table 13 -- Holding times at lower temperatures		46
Table 14 -- Weld inspections of primary and secondary liquid container		48

Table 15 -- Extent of radiographic/ultrasonic examination of shell welds of primary and secondary liquid container	48
Table 16 -- Inspection of vapour barrier/liner	50
Table 17 -- Extent of radiographic and ultrasonic examination of shell plate welds of vapour containers	51
Table A.1 -- Static action	55
Table A.2 -- Cyclic action	55
Table A.3 -- Accidental action	55