

# DIN EN 14620-3:2006-12 (E)

Design and manufacture of site built, vertical, cylindrical, flat-bottomed steel tanks for the storage of refrigerated, liquefied gases with operating temperatures between 0 °C and -165 °C - Part 3: Concrete components

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	5
4	General .....	5
5	Vapour tightness .....	6
6	Materials .....	6
6.1	General .....	6
6.2	Concrete .....	6
6.3	Pre-stressing and reinforcing steel .....	6
7	Design .....	7
7.1	General .....	7
7.2	Partial factors for actions and combinations of actions .....	7
7.3	Liquid tightness .....	7
8	Detailing provisions .....	8
8.1	General .....	8
8.2	Pre-stressing .....	8
8.3	Wall design .....	8
8.4	Steel roof liner .....	8
8.5	Construction joints .....	8
8.6	Position of tendons and wires .....	8
8.7	Concrete cover .....	9
8.8	Minimum reinforcement .....	9
8.9	Reinforced concrete bund walls .....	9
9	Construction and workmanship .....	9
9.1	General .....	9
9.2	Crack control .....	9
9.3	Formwork and tie-rods .....	9
9.4	Spacers .....	10
9.5	Curing .....	10
9.6	Tolerances .....	10
10	Liners and coatings .....	10
10.1	General .....	10
10.2	Liners .....	10
10.3	Coatings .....	10
10.4	Thermal Protection System (TPS) .....	11
Annex A (informative) Materials .....		12

<b>Annex B (informative) Pre-stressed concrete tank .....</b>	<b>15</b>
<b>Bibliography .....</b>	<b>21</b>
<b>Figures Figure A.1 -- Notch on reinforcement bar .....</b>	<b>14</b>
<b>Figure B.1 -- Typical joints for pre-stressed wall and base junction .....</b>	<b>17</b>
<b>Tables Table 1 -- Partial load factors for accidental actions .....</b>	<b>7</b>
<b>Table B.1 -- Summary of the advantages and disadvantages of joints in the wall to base junction ...</b>	<b>16</b>