

# ISO 5167-1:2003-03 (E)

## Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 1: General principles and requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols and subscripts .....	6
4.1	Symbols .....	6
4.2	Subscripts .....	7
5	Principle of the method of measurement and computation .....	7
5.1	Principle of the method of measurement .....	7
5.2	Method of determination of the diameter ratio of the selected standard primary device .....	8
5.3	Computation of flowrate .....	8
5.4	Determination of density, pressure and temperature .....	8
6	General requirements for the measurements .....	10
6.1	Primary device .....	10
6.2	Nature of the fluid .....	11
6.3	Flow conditions .....	11
7	Installation requirements .....	11
7.1	General .....	11
7.2	Minimum upstream and downstream straight lengths .....	13
7.3	General requirement for flow conditions at the primary device .....	13
7.4	Flow conditioners (see also Annex C) .....	13
8	Uncertainties on the measurement of flowrate .....	16
8.1	Definition of uncertainty .....	16
8.2	Practical computation of the uncertainty .....	17
Annex A (informative)	Iterative computations .....	19
Annex B (informative)	Examples of values of the pipe wall uniform equivalent roughness, k .....	21
Annex C (informative)	Flow conditioners and flow straighteners .....	22
Bibliography .....		33