# ISO/TR 12767:2007-09 (E)

## Measurement of fluid flow by means of pressure differential devices - Guidelines on the effect of departure fro m the specifications and operating conditions given in ISO 5167

## Contents

Page


Foreword ..... iv

Introduction ..... v

1 Scope ..... 1

2 Normative references ..... 1

3 Terms and definitions ..... 2

4 Symbols and abbreviated terms ..... 2

5 Effect of errors on flowrate calculations ..... 3
5.1 General ..... 3
5.2 Quantifiable effects ..... 3

6 Effects of deviations in construction ..... 4
6.1 Orifice-plate edge sharpness ..... 4
6.2 Thickness of orifice edge ..... 5
6.3 Condition of upstream and downstream faces of orifice plate ..... 6
6.4 Position of pressure tappings for an orifice ..... 6
6.5 Condition of pressure tappings ..... 7

7 Effects of pipeline near the meter ..... 7
7.1 Pipe diameter ..... 7
7.2 Steps and taper sections ..... 8
7.3 Diameter of carrier ring ..... 8
7.4 Undersize joint rings ..... 11
7.5 Protruding welds ..... 11
7.6 Eccentricity ..... 11

8 Effects of pipe layout ..... 14
8.1 General ..... 14
8.2 Discharge coefficient compensation ..... 14
8.3 Pressure tappings ..... 16
8.4 Devices for improving flow conditions ..... 17

9 Operational deviations ..... 17
9.1 General ..... 17
9.2 Deformation of an orifice plate ..... 17
9.3 Deposition on the upstream face of an orifice plate ..... 19
9.4 Deposition in the meter tube ..... 23
9.5 Orifice-plate edge sharpness ..... 23
9.6 Deposition and increase of surface roughness in Venturi tubes ..... 24

10 Pipe roughness ..... 26
10.1 General ..... 26
10.2 Upstream pipe ..... 27
10.3 Downstream pipe ..... 30
10.4 Reduction of roughness effects ..... 30
10.5 Maintenance ..... 30

Bibliography ..... 32