

# ISO 3966:2008-07 (E)

## Measurement of fluid flow in closed conduits - Velocity area method using Pitot static tubes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Symbols and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Principle .....</b>	<b>4</b>
<b>5</b>	<b>Design of Pitot tubes .....</b>	<b>7</b>
<b>6</b>	<b>Requirements for use of Pitot tubes .....</b>	<b>8</b>
<b>7</b>	<b>Positioning of Pitot tube .....</b>	<b>11</b>
<b>8</b>	<b>Velocity computation .....</b>	<b>11</b>
<b>9</b>	<b>Determination of the discharge velocity by graphical integration of the velocity area .....</b>	<b>14</b>
<b>10</b>	<b>Determination of the discharge velocity by numerical integration of the velocity area .....</b>	<b>17</b>
<b>11</b>	<b>Determination of the discharge velocity by arithmetical methods .....</b>	<b>19</b>
<b>12</b>	<b>Corrections of local velocity measurements .....</b>	<b>23</b>
<b>13</b>	<b>Errors .....</b>	<b>28</b>
	<b>Annex A (normative) Pitot tubes .....</b>	<b>34</b>
	<b>Annex B (normative) Correction to the measuring position of Pitot tubes used in a transverse velocity gradient .....</b>	<b>39</b>
	<b>Annex C (normative) Study concerning turbulence correction .....</b>	<b>41</b>
	<b>Annex D (normative) Damping of pressure gauges .....</b>	<b>44</b>
	<b>Annex E (normative) Measurements with a Pitot tube in a compressible fluid .....</b>	<b>46</b>
	<b>Annex F (normative) Determination of coefficient m for extrapolation near the wall .....</b>	<b>50</b>
	<b>Annex G (normative) Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes .....</b>	<b>51</b>
	<b>Bibliography .....</b>	<b>54</b>