

# ISO 7194:2008-07 (E)

## Measurement of fluid flow in closed conduits - Velocity-area methods of flow measurement in swirling or asymmetric flow conditions in circular ducts by means of current-meters or Pitot static tubes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1 <b>Scope</b> .....		1
2 <b>Normative references</b> .....		1
3 <b>Symbols</b> .....		2
4 <b>Principle</b> .....		2
5 <b>Choice of measuring plane</b> .....		3
6 <b>Devices for improving flow conditions</b> .....		3
7 <b>Measurement of local velocities</b> .....		7
8 <b>Determination of mean flow velocity</b> .....		14
9 <b>Accuracy of flow-rate estimation</b> .....		14
<b>Annex A (normative) Detection and removal of regular pressure fluctuations</b> .....		17
<b>Annex B (normative) Damping of manometers</b> .....		18
<b>Annex C (normative) Calculation of Pitot static tube locations for method B</b> .....		20
<b>Annex D (normative) Corrections to be applied when a Pitot static tube is used</b> .....		22
<b>Annex E (normative) Corrections to be applied when a current-meter is used</b> .....		23
<b>Annex F (normative) Errors due to non-axisymmetrical velocity distribution</b> .....		26
<b>Bibliography</b> .....		27