ISO 10360-2:2009-12 (E)

Geometrical product specifications (GPS) - Acceptance and reverification tests for coordinate measuring machines (CMM) - Part 2: CMMs used for measuring linear dimensions

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols 4

5 Environmental and metrological requirements 4
5.1 Environmental conditions 4
5.2 Operating conditions 5
5.3 Length measurement error, EL 5
5.4 Repeatability range of the length measurement error, R0 5
5.5 Workpiece loading effects 5

6 Acceptance tests and reverification tests 6
6.1 General 6
6.2 Principle 6
6.3 Length measurement error with zero ram axis stylus tip offset, E0 7
6.3.1 General 7
6.3.2 Measuring equipment 7
6.3.3 Procedure 8
6.3.4 Derivation of test results 9
6.4 Repeatability range of the length measurement error, R0 9
6.5 Length measurement error with ram axis stylus tip offset of 150 mm, E150 10
6.5.1 Measuring equipment 10
6.5.2 Procedure 10
6.5.3 Derivation of test results 12
6.6 Dual ram CMMs 12
6.6.1 Simplex operating mode 12
6.6.2 Duplex operating mode 12

7 Compliance with specifications 13
7.1 Acceptance test 13
7.1.1 Acceptance criteria 13
7.1.2 Data rejection and repeated measurements 14
7.2 Reverification test 14

8 Applications 14
8.1 Acceptance test 14
8.2 Reverification test 15
8.3 Interim check 15

9 Indication in product documentation and data sheets 15

Annex A (informative) Interim check **16**

Annex B (normative) Artefacts that represent a calibrated test length **18**

Annex C (informative) Alignment of gauges **23**

Annex D (normative) Mathematical adjustments to low CTE artefacts **25**

Annex E (informative) Location of the single stylus probing test **27**

Annex F (informative) Relation to the GPS matrix model **28**

Bibliography **29**