

# ISO 3040:2009-12 (E)

## Geometrical product specifications (GPS) - Dimensioning and tolerancing - Cones

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Graphical symbol for a cone .....</b>	<b>2</b>
<b>5</b>	<b>Dimensioning of cones .....</b>	<b>2</b>
<b>5.1</b>	<b>Characteristics of cones .....</b>	<b>2</b>
<b>5.2</b>	<b>Indication of rate of taper on drawings .....</b>	<b>4</b>
<b>5.3</b>	<b>Standardized series of cones .....</b>	<b>4</b>
<b>6</b>	<b>Tolerancing of cones .....</b>	<b>5</b>
<b>6.1</b>	<b>General .....</b>	<b>5</b>
<b>6.2</b>	<b>Tolerancing of cone, cone angle specified .....</b>	<b>5</b>
<b>6.3</b>	<b>Tolerancing of cone; rate of taper specified .....</b>	<b>6</b>
<b>6.4</b>	<b>Tolerancing zone of cone simultaneously defining the axial location of the cone .....</b>	<b>7</b>
<b>6.5</b>	<b>Tolerancing of cone relative to a datum system (simultaneously defining coaxiality) .....</b>	<b>8</b>
<b>Annex A (informative)</b>	<b>Former practice -- Tolerancing of cone separate from the tolerance of the axial location of the cone .....</b>	<b>9</b>
<b>Annex B (informative)</b>	<b>Relation to the GPS matrix model .....</b>	<b>10</b>
<b>Bibliography .....</b>		<b>11</b>