

ISO 9493:2010-11 (E)

Geometrical product specifications (GPS) - Dimensional measuring equipment: Dial test indicators (lever type) - Design and metrological characteristics

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Design characteristics | 2 |
| 4.1 | General design features | 2 |
| 4.2 | Type | 2 |
| 4.3 | Nomenclature | 4 |
| 4.4 | Dovetail mounting | 4 |
| 4.5 | Dial and pointer | 5 |
| 4.6 | Stylus | 6 |
| 4.7 | Zero adjustment | 7 |
| 4.8 | Design characteristics (manufacturer's specification) | 7 |
| 5 | Metrological characteristics | 7 |
| 5.1 | Maximum permissible error (MPE) and maximum permissible limit (MPL) for a number of metrological characteristics | 7 |
| 5.2 | Stylus | 8 |
| 5.3 | Measuring forces | 8 |
| 6 | Proving of conformance with specification | 8 |
| 6.1 | General | 8 |
| 6.2 | Measurement standards for calibration of metrological characteristics | 8 |
| 7 | Marking | 8 |
| Annex A (informative) Examples of a diagram of errors of indication | | 9 |
| Annex B (informative) Example of data sheet for dial test indicators | | 11 |
| Annex C (informative) Calibration of metrological characteristics | | 13 |
| Annex D (informative) Notes on use | | 15 |
| Annex E (informative) Relation to the GPS matrix model | | 17 |
| Bibliography | | 19 |