

ISO 17089-2:2012-10 (E)

Measurement of fluid flow in closed conduits - Ultrasonic meters for gas - Part 2: Meters for industrial applications

| Contents | | Page |
|---|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, and symbols | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Symbols and subscripts | 6 |
| 3.3 | Abbreviations | 7 |
| 4 | Principles of measurement | 7 |
| 4.1 | Transit time ultrasonic meters | 7 |
| 4.2 | Flare or vent gas meters | 8 |
| 4.3 | Factors affecting performance | 9 |
| 4.4 | Description of generic types | 9 |
| 4.5 | Impact of pressure and temperature on the flowmeter geometry | 14 |
| 4.6 | USM measurement uncertainty determination | 14 |
| 4.7 | USM classification | 14 |
| 5 | Meter characteristics | 15 |
| 5.1 | Performance indications | 15 |
| 5.2 | Operating conditions | 15 |
| 5.3 | Meter body, materials, and construction | 15 |
| 5.4 | Connections | 16 |
| 5.5 | Dimensions | 16 |
| 5.6 | Ultrasonic ports | 16 |
| 5.7 | Pressure tapping | 16 |
| 5.8 | Anti-roll provision | 16 |
| 5.9 | Flow conditioner | 17 |
| 5.10 | Markings | 17 |
| 5.11 | Transducers | 17 |
| 5.12 | Electronics | 17 |
| 5.13 | Firmware and software | 18 |
| 5.14 | Inspection and verification functions | 19 |
| 5.15 | Operation and installation requirements | 19 |
| 5.16 | Installation requirements and flow profile considerations | 21 |
| 5.17 | Handling and transportation | 22 |
| 6 | Test and calibration | 23 |
| 6.1 | Flow test and calibration | 23 |
| 6.2 | Static testing for leakage and pressure | 23 |
| 6.3 | Dimensional measurements | 23 |
| 6.4 | Dynamic testing (testing and calibration, adjustment under flowing conditions) | 25 |
| 6.5 | Meter diagnostics | 26 |
| 6.6 | In situ verification | 27 |
| Annex A (normative) Special application note on valve characterization and noise | | 29 |
| Bibliography | | 36 |