ISO 12764:2017-08 (E)

Measurement of fluid flow in closed conduits - Flowrate measurement by means of vortex shedding flowmeters inserted in circular cross-section conduits running full

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1
3.1 Definitions specific to this vortex flowmeter standard 2
3.2 Definitions related to measurement of fluid flow in closed conduits 3
3.3 Definitions related to the vocabulary used in metrology 4

4 Symbols and subscripts 4
4.1 Symbols 4
4.2 Subscripts 5

5 Principle 5
5.1 Bluff body 5
5.2 Shedding vortices detection/sensors 6
5.3 Strouhal number 6

6 Flowmeter description 7
6.1 Physical components 7
6.1.1 Flow tube 8
6.1.2 System output 8
6.2 Marking 9
6.3 Safety issues 9
6.3.1 Pressure and fluid-wetted parts 9
6.3.2 In-line instrumentation, testing 9
6.3.3 Materials 9

7 Application 9
7.1 Sizing 9
7.2 Pressure loss and cavitation 10
7.3 Swirl and undeveloped profile 10
7.4 Flow stability 11
7.5 Vibration 11

8 Installation 11
8.1 General 11
8.2 Installation location 11
8.3 Piping 11
8.3.1 Straight sections 11
8.3.2 Mating pipe 12
8.3.3 Position of valves 12
8.3.4 Dual phase flow 12
8.3.5 Bypass 12
8.3.6 Additional process measurements for compensation 12
8.3.7 Installation orientation, electronics 13
8.3.8 Bluff body orientation 13

8.3.9 Full pipe condition 13
8.3.10 Condensable gas 13
8.3.11 Extreme conditions 13
8.3.12 New installations 14

9 Operation 14
9.1 Operating limits 14
9.2 Start-up procedure 14
9.3 Shift of calibration 14
9.4 Maintenance 14

10 Performance characteristics 14

10.1 Reynolds number range 14
10.2 P-T conditions 14
10.3 Performance disturbing influences 14

11 Calibration (K-factor determination) 15
11.1 Mean K-factor 15
11.2 In situ calibration 15

Annex A (informative) Period jitter and its effects on calibration 16

Annex B (informative) Special considerations for steam 18

Bibliography 22