

DIN 16003:2018-04 (E)

Mechanical pressure and temperature gauges - Differential pressure gauges - Dimensions, metrology, requirements and testing

| Contents | | Page |
|----------|--|------|
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 6 |
| 4 | Nominal sizes | 6 |
| 5 | Pressure ranges | 6 |
| 6 | Accuracy classes | 7 |
| 7 | Dimensions | 8 |
| 7.1 | General tolerances | 8 |
| 7.2 | Cases and flanges | 8 |
| 7.3 | Pressure connections | 9 |
| 7.3.1 | General | 9 |
| 7.3.2 | Centre-to-centre distances for the pressure connections | 9 |
| 7.3.3 | Gaskets | 10 |
| 7.4 | Type of mounting and position of the connection | 10 |
| 8 | Pressure connections and pressure ranges | 13 |
| 9 | Requirements | 13 |
| 9.1 | Measurement accuracy | 13 |
| 9.2 | Hysteresis | 14 |
| 9.3 | Effect of the static pressure | 14 |
| 9.4 | Temperature effect | 14 |
| 9.5 | Endurance | 14 |
| 9.5.1 | General | 14 |
| 9.5.2 | Steady pressure load | 14 |
| 9.5.3 | Over-pressure (one-sided exposure to pressure) | 14 |
| 9.5.4 | Cyclic pressure | 14 |
| 9.6 | Operating conditions | 15 |
| 9.6.1 | Operating temperature range | 15 |
| 9.6.2 | Temperature range for storage | 15 |
| 9.6.3 | Protection against ingress of water and foreign particles (degree of protection) | 15 |
| 9.6.4 | Effect of mechanical shock | 15 |
| 9.6.5 | Effect of mechanical vibration | 15 |
| 9.6.6 | Leak rate | 15 |
| 9.6.7 | Mounting position | 15 |
| 9.7 | Dials and pointers | 15 |
| 9.7.1 | Scale angle | 15 |
| 9.7.2 | Scale interval | 15 |
| 9.7.3 | Scale marks | 15 |
| 9.7.4 | Scale numbering | 15 |
| 9.7.5 | Pointer dimensions | 16 |
| 9.7.6 | Knife edge pointer | 16 |
| 9.7.7 | Information on the dial | 16 |
| 9.7.8 | Pointer stop | 17 |
| 9.8 | Safety | 17 |

| | | |
|-------------|--|--------|
| 9.8.1 | General | 17 |
| 9.8.2 | Pressure gauges with blow-out device | 17 |
| 9.8.3 | Safety pattern gauges | 17 |
| 9.9 | Pressure gauges for oxygen or acetylene | 18 |
| 9.10 | Liquid-filled pressure gauges | 18 |
| 9.11 | Additional design requirements for pressure gauges in legal metrology | 18 |
| 10 | Testing | 18 |
| 10.1 | General | 18 |
| 10.2 | Type approval and production piece tests | 19 |
| 10.3 | Accuracy, hysteresis and effect of static pressure | 21 |
| 10.3.1 | Accuracy and hysteresis | 21 |
| 10.3.2 | Effect of the static pressure | 21 |
| 10.4 | Temperature effect | 21 |
| 10.5 | Endurance | 21 |
| 10.5.1 | General | 21 |
| 10.5.2 | Exposure to static pressure and over-pressure | 21 |
| 10.5.3 | Cyclic pressure | 21 |
| 10.6 | Accuracy after endurance test | 21 |
| 10.7 | Operating temperature range | 21 |
| 10.8 | Temperature range for storage | 22 |
| 10.9 | Protection against ingress of water and foreign particles (degree of protection) | 22 |
| 10.10 | Effects of mechanical shock | 22 |
| 10.11 | Effects of mechanical vibration | 22 |
| 10.12 | Leak test | 22 |
| 10.13 | Mounting position | 22 |
| 10.14 | Safety | 22 |
| 10.14.1 | Pressure gauges with blow-out device | 22 |
| 10.14.2 | Safety pattern gauges | 22 |
| 11 | Packaging for transportation | 23 |
| 12 | Designation | 24 |
| Figures | Figure 1 -- Dimensions | 8 |
| | Figure 2 -- Pressure connections | 10 |
| | Figure 3 -- Example of information on the dial (corresponds to the example in Clause 12) | 16 |
| Tables | Table 1 -- Preferred pressure ranges for differential pressure | 7 |
| | Table 2 -- Nominal size compared to the accuracy class | 7 |
| | Table 3 -- Dimensions | 9 |
| | Table 4 -- Preferred centre-to-centre distances | 9 |
| | Table 5 -- Preferred type of mounting and position of connections | 10 |
| | Table 6 -- Minimum length of pointer | 16 |
| | Table 7 -- Type approval and production piece tests | 20 |