

ISO/TR 15377:2018-01 (E)

Measurement of fluid flow by means of pressure-differential devices - Guidelines for the specification of orifice plates, nozzles and Venturi tubes beyond the scope of ISO 5167

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	1
5	Square-edged orifice plates and nozzles: With drain holes, in pipes below 50 mm diameter, and as inlet and outlet devices	3
5.1	Drain holes through the upstream face of the square-edged orifice plate or nozzle	3
5.1.1	General	3
5.1.2	Square-edged orifice plates	3
5.1.3	ISA 1932 nozzles	5
5.1.4	Long radius nozzles	5
5.2	Square-edged orifice plates installed in pipes of diameter 25 mm $D < 50$ mm	5
5.2.1	General	5
5.2.2	Limits of use	5
5.2.3	Discharge coefficients and corresponding uncertainties	6
5.3	No upstream or downstream pipeline	6
5.3.1	General	6
5.3.2	Flow from a large space (no upstream pipeline) into a pipeline or another large space	6
5.3.3	Flow into a large space (no downstream pipeline)	8
6	Orifice plates (except square-edged)	9
6.1	Conical entrance orifice plates	9
6.1.1	General	9
6.1.2	Limits of use	9
6.1.3	Description	10
6.1.4	Pressure tapplings	13
6.1.5	Coefficients and corresponding uncertainties	14
6.2	Quarter-circle orifice plates	14
6.2.1	General	14
6.2.2	Limits of use	14
6.2.3	Description	15
6.2.4	Pressure tapplings	18
6.2.5	Coefficients and corresponding uncertainties	18
6.3	Eccentric orifice plates	19
6.3.1	General	19
6.3.2	Limits of use	20
6.3.3	Description	20
6.3.4	Coefficients and corresponding uncertainties	23
7	Venturi tubes with machined convergent of angle $10,5^\circ$	25
7.1	General	25
7.2	Description	25
7.3	Limits of use	25

7.4	Discharge coefficient	26
7.5	Expansibility [expansion] factor	26
7.6	Pressure loss	26
7.7	Installation requirements	26
Annex A (informative) An example of the calculations in 5.1.2		28
Bibliography		31