ISO 14405-2:2018 (E)

Geometrical product specifications (GPS) — Dimensional tolerancing — Part 2: Dimensions other than linear or angular sizes

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Principles and rules for indication of dimensions and related tolerances

5 Units used in drawings for dimensions

6 Indication of tolerances for linear or angular dimensions

7 Illustrations of ambiguous ± tolerancing vs. unambiguous geometrical specifications

- 7.1 General
- 7.2 Linear distance between two integral features
- 7.3 Linear distance between an integral and a derived feature
- 7.4 Linear distance between two derived features
- 7.5 Radius dimension
- 7.6 Linear distance between non-planar integral features
- 7.7 Linear distance in two directions

8 Angular tolerancing

- 8.1 Examples of geometrical specifications applied to angular distance between two integral features
- 8.2 Angular distance between an integral feature and a derived feature

Annex A (informative) Explanations and examples of the ambiguity caused by using ± tolerances for dimensions other than linear size or angular size

- A.1 Introduction
- A.2 Linear distance between two parallel integral features facing the same direction
- A.3 Linear distance between two parallel integral features facing the opposite direction
- A.4 Linear distance between an integral and a derived feature
- A.5 Linear distance between two derived features
- A.6 Radius dimension for an integral feature
- A.7 Radius dimension for a derived feature
- A.8 Linear distance between two non-planar integral features
- A.9 Linear distance in two directions
- A.10 Angular distance between an integral feature and a derived feature
- A.11 Rounding and chamfers
- A.12 Arc length

Annex B (informative) Relation to the GPS matrix model

- B.1 General
- B.2 Information about this document and its use
- B.3 Position in the GPS matrix model
- B.4 Related standards

Page count: 22