DIN EN ISO 5167-6:2020-02 (E)

Measurement of fluid flow by means of pressure diffe rential devices inserted in circular cross-section conduits running full - Part 6: Wedge meters (ISO 5167-6:2019)

Contents

Page

European foreword 3

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Principles of the method of measurement and computation 7

5 Wedge meters 8
- 5.1 Field of application 8
- 5.2 General shape 9
- 5.3 Material and manufacture 10
- 5.4 Pressure tappings 10
- 5.5 Discharge coefficient, C 11
  - 5.5.1 Limits of use 11
  - 5.5.2 Discharge coefficient of the wedge meter 11
- 5.6 Expansibility [expansion] factor, ε 12
- 5.7 Uncertainty of the discharge coefficient, C 12
- 5.8 Uncertainty of the expansibility [expansion] factor, ε 12
- 5.9 Pressure loss 12

6 Installation requirements 13
- 6.1 General 13
- 6.2 Minimum upstream and downstream straight lengths for installations between various fittings and the wedge meter 13
- 6.3 Additional specific installation requirements for wedge meters 13
  - 6.3.1 Circularity and cylindricality of pipes upstream and downstream of the wedge meter 13
  - 6.3.2 Roughness of the upstream and downstream pipe 14
  - 6.3.3 Positioning of a thermowell 14
  - 6.3.4 Bidirectional wedge meters 14

7 Flow calibration of wedge meters 14
- 7.1 General 14
- 7.2 Test facility 14
- 7.3 Meter installation 14
- 7.4 Design of the test programme 15
- 7.5 Reporting the calibration results 15
- 7.6 Uncertainty analysis of the calibration 15
  - 7.6.1 General 15
  - 7.6.2 Uncertainty of the test facility 15
  - 7.6.3 Uncertainty of the wedge meter 15

Annex A (informative) **Table of expansibility [expansion] factor** 16

Annex B (informative) **Use of Kd^2 parameter** 17

Bibliography 18