

ISO 3966:2020 (E)

Measurement of fluid flow in closed conduits — Velocity area method using Pitot static tubes

Contents

	Foreword
1	Scope
2	Normative references
3	Terms, definitions and symbols
3.1	Terms and definitions
3.2	Symbols
4	Principle
4.1	General principle
4.1.1	Graphical integration of the velocity area (see Clause 9)
4.1.2	Numerical integration of the velocity area (see Clause 10)
4.1.3	Arithmetical methods (see Clause 11)
4.2	Measurement of the measuring cross-section
4.2.1	Circular cross-sections
4.2.2	Rectangular cross-sections
4.3	Measurement of local velocities
4.3.1	Method of exploring traverse section
4.3.2	Reference measurement
4.3.3	Checking of velocity distribution
4.4	Location and number of measuring points in the cross-section
4.4.1	General requirements
4.4.2	Circular cross-sections
4.4.3	Rectangular cross-sections
5	Design of Pitot tubes
5.1	General description
5.2	Criteria to be fulfilled by the Pitot tube
6	Requirements for use of Pitot tubes
6.1	Selection of the measuring cross-section
6.1.1	Location of the measuring cross-section (of selection)
6.1.2	Avoidance of asymmetry, swirl and turbulences
6.1.3	Maximum flow deviation
6.1.4	Preliminary traverse tests
6.2	Devices for improving flow conditions
6.2.1	Anti-swirl device
6.2.2	Profile developer
6.2.3	Positioning/Location of devices
6.2.4	Provisional guiding installation
6.3	Limits of use
6.3.1	Nature of the fluid
6.3.2	Range of velocities
6.3.3	Nature of the flow
6.3.4	Dimensional limitations
6.3.5	Influence of turbulence
6.4	Performance of measurements
6.4.1	Measurement of differential pressure
6.4.2	Differential pressure fluctuations
6.4.3	Determination of fluid density
6.5	Inspection and maintenance of the Pitot tube

- 7 **Positioning of Pitot tube**
- 8 **Velocity computation**
 - 8.1 **Verification of conditions for a measurement**
 - 8.2 **Formulae for velocity computation**
- 9 **Determination of the discharge velocity by graphical integration of the velocity area**
 - 9.1 **Circular cross-section**
 - 9.2 **Rectangular cross-sections**
- 10 **Determination of the discharge velocity by numerical integration of the velocity area**
 - 10.1 **Circular cross-sections**
 - 10.2 **Rectangular cross-sections**
- 11 **Determination of the discharge velocity by arithmetic methods**
 - 11.1 **“Log-linear” method**
 - 11.1.1 **Circular cross-sections**
 - 11.1.2 **Rectangular cross-sections**
 - 11.2 **Log-Chebyshev method**
 - 11.2.1 **Circular cross-sections**
 - 11.2.2 **Rectangular cross-sections**
- 12 **Corrections of local velocity measurements**
 - 12.1 **Correction for stem blockage**
 - 12.1.1 **Case where the correction can be neglected**
 - 12.1.2 **Estimation of the correction of local velocity measurement**
 - 12.1.3 **Estimation of the overall correction of the flow-rate value (application to arithmetic methods)**
 - 12.2 **Correction for transverse velocity gradient**
 - 12.2.1 **Correction for measuring point position**
 - 12.2.1.1 **Case of graphical or numerical integration**
 - 12.2.1.2 **Case of arithmetical methods**
 - 12.2.2 **Overall correction of flow rate**
 - 12.3 **Correction for turbulence**
 - 12.4 **Correction for head loss**
- 13 **Errors**
 - 13.1 **Definition of the error**
 - 13.2 **Errors in the estimation of the local velocity**
 - 13.2.1 **Random errors**
 - 13.2.1.1 **Error in the measurement of differential pressure**
 - 13.2.1.2 **Error due to slow velocity fluctuations**
 - 13.2.1.3 **Error in density**
 - 13.2.1.4 **Error in the calculation of the compressibility correction**
 - 13.2.2 **Systematic errors**
 - 13.2.2.1 **Error in the Pitot tube calibration**
 - 13.2.2.2 **Error due to turbulence**
 - 13.2.2.3 **Error due to the transverse velocity gradient**
 - 13.2.2.4 **Error due to conduit blockage**
 - 13.2.2.5 **Error due to the inclination of the Pitot tube with respect to the flow direction**
 - 13.2.2.6 **Error due to the head loss between total and static pressure tappings**
 - 13.3 **Errors in the estimation of flow rate**
 - 13.3.1 **Random errors**
 - 13.3.1.1 **Error due to local velocity measurements**
 - 13.3.1.2 **Error due to graph in graphical integration technique**
 - 13.3.1.3 **Error due to evaluation of power law index, m**
 - 13.3.1.4 **Error due to positioning Pitot tubes**
 - 13.3.2 **Systematic errors**
 - 13.3.2.1 **Error due to measurement of duct dimensions**
 - 13.3.2.2 **Error due to numerical or arithmetic integration techniques**
 - 13.3.2.3 **Error due to number of measuring points**
 - 13.4 **Definition of the standard deviation⁵ 5 The standard deviation as defined here is what is more accurately referred to as the “standard deviation estimation” by statisticians.**

- 13.5 Definition of the tolerance
 - 13.6 Calculation of standard deviation
 - 13.6.1 Standard deviation on local velocity measurement
 - 13.6.2 Standard deviation on flow-rate measurement
- Annex A (normative) Pitot tubes**
- A.1 Different types
 - A.2 Sensitivity of Pitot tube to inclination
- Annex B (normative) Correction to the measuring position of Pitot tubes used in a transverse velocity gradient**
- B.1 Determination of the displacement of a measuring point
 - B.2 Determination of the overall correction for flow rate in a circular conduit
- Annex C (normative) Study concerning turbulence correction**
- C.1 Influence of turbulence on the total pressure tap
 - C.1.1 Pressure probe insensitive to orientation
 - C.1.2 Pressure probe sensitive to orientation
 - C.2 Influence of turbulence on the static-pressure tap
 - C.3 Evaluation of errors for an exploration with a Pitot tube
- Annex D (normative) Damping of pressure gauges**
- D.1 Damping procedure
 - D.2 Balancing of the damping
 - D.3 Checking of the damping
- Annex E (normative) Measurements with a Pitot tube in a compressible fluid**
- E.1 General
 - E.2 List of subscripts used in this annex
 - E.3 Determination of velocity calculation
 - E.4 Operating procedure
- Annex F (normative) Determination of coefficient m for extrapolation near the wall**
- F.1 Method of determination of m
 - F.2 Influence on the calculation of discharge velocity
- Annex G (informative) Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes**
- G.1 Error on the local velocity measurement
 - G.2 Error on the flow-rate measurement

Page count: 55