

DIN EN ISO 2692:2022-08 (E)

Geometrical products specifications (GPS) - Geometrical tolerancing - Maximum material requirement (MMR), least material requirement (LMR) and reciprocity requirement (RPR) (ISO 2692 :2021)

Contents		Page
European foreword		3
Foreword		4
Introduction		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Maximum material requirement (MMR) and least material requirement (LMR)	11
4.1	General	11
4.1.1	MMVS or LMVS specification	11
4.1.2	Indirect determination of MMVS or LMVS	11
4.1.3	Direct indication of MMVS or LMVS	12
4.1.4	MMR or LMR applied to several toleranced features	13
4.1.5	Simultaneous requirement	13
4.1.6	MMR or LMR on a datum without MMR or LMR on the toleranced feature	13
4.2	Maximum material requirement (MMR)	13
4.2.1	MMR for toleranced features with indirect determination of virtual size	13
4.2.2	MMR for related datum features with indirect determination of virtual size	14
4.2.3	MMR for toleranced features with direct indication of virtual size	16
4.2.4	MMR for related datum features with direct indication of virtual size	16
4.3	Least material requirement (LMR)	17
4.3.1	LMR for toleranced features with indirect determination of virtual size	17
4.3.2	LMR for related datum features with indirect determination of virtual size	18
4.3.3	LMR for toleranced features with direct indication of virtual size	19
4.3.4	LMR for related datum features with direct indication of virtual size	20
5	Reciprocity requirement (RPR)	21
5.1	General	21
5.2	Reciprocity requirement (RPR) and maximum material requirement (MMR)	21
5.3	Reciprocity requirement (RPR) and least material requirement (LMR)	21
Annex A (informative)	Examples of tolerancing with , and	22
Annex B (informative)	Former practice	54
Annex C (informative)	Concept diagram	55
Annex D (informative)	Use of symbols for geometrical characteristics with or	57
Annex E (informative)	Relation to the GPS matrix model	59
Bibliography		60