DIN EN ISO 10360-13:2023-11 (E)

Geometrical product specifications (GPS) - Acceptance and reverification tests for coordinate measuring systems (CMS) - Part 13: Optical 3D CMS (ISO 10360-13:2021)

Contents

Page

European foreword 5

Foreword 6

Introduction 7

1 Scope 9

2 Normative references 9

3 Terms and definitions 9

4 Symbols 14

5 Rated operating conditions 14
5.1 Environmental conditions 14
5.2 Operating conditions 15
5.2.1 General 15
5.2.2 Material and surface characteristic of material standards 15
5.2.3 Pre-processing 16

6 Acceptance and reverification test 16
6.1 General 16
6.2 Distortion characteristics 16
6.2.1 General 16
6.2.2 Distortion error 16
6.3 Probing characteristics 20
6.3.1 Principle 20
6.3.2 Material standard 20
6.3.3 Procedure 21
6.3.4 Derivation of test results 21
6.3.5 Flat-form distortion error 22
6.4 Volumetric length measurement error in concatenated measurement volume 25
6.4.1 Principle 25
6.4.2 Material standard 25
6.4.3 Low CTE case 25
6.4.4 Procedure 26
6.4.5 Derivation of test results 28

7 Conformity with the specification 28
7.1 Acceptance test 28
7.1.1 Acceptance criteria 28
7.2 Reverification test 30

8 Applications 31
8.1 Acceptance test 31
8.2 Reverification test 31
8.3 Interim check 31

9 Indication in product documentation and data sheets 31

Annex A (informative) Evaluation of bi-directional length measurement characteristics 32

A.1 General 32
A.2 Derivation of bi-directional length measurement test results 32
A.2.1 General 32
A.2.2 Bi-directional length measurement error compounded from test results based on point cloud 32
A.3 Indication in product documentation and data sheets 33

Annex B (normative) Artefacts that represent a calibrated test length and corresponding measurement procedures 34

B.1 General 34
B.2 Artefact and procedure for realizing calibrated test length 35
B.2.1 General 35
B.2.2 Ball plates or ball bars measured in a centre-to-centre manner by point cloud 35
B.2.3 Laser interferometry measured in a centre-to-centre manner 35
B.2.4 Step gauges measured in a face-to-face manner 36
B.2.5 CMM positioning the gauging surface(s) 36

Annex C (informative) Procedure of concatenated length measurement to assess the influence of the concatenation path on error 37

C.1 General 37
C.2 Concatenated length measurement through detoured concatenation pathway 37
C.3 Example of detoured concatenation pathway 38

Annex D (informative) Alignment of artefacts 41

D.1 General 41
D.2 Parallel face artefacts 41
D.3 Ball bar 41

Annex E (informative) Surface characteristic of material standard 43

E.1 General 43
E.2 Surface characteristics of material standards potentially impacting measuring performance of optical 3D CMS 43
E.2.1 Colour 43
E.2.2 Glossiness 43
E.2.3 Roughness 43
E.2.4 Other optical characteristics attributed to surface sublayer 44
E.2.5 Evaluation of surface characteristics 44
E.3 Potential impact behind surface characteristics restricted in the main text of this document 44
E.4 Possible performance evaluation of optical 3D CMS with influence of surface characteristics of material standards 44
E.4.1 Usage of optical spectral transmittancy of colour filter to emulate different surface colour 44
E.4.2 Usage of equivalent optical attenuation means to emulate different surface colour in cases of monochromatic optical 3D CMS 45
E.4.3 Usage of material standards having identical nominal geometries but different intended surface characteristics 46

Annex F (informative) Structural resolution test 47

F.1 General 47
F.2 Test method 47
F.2.1 General 47
F.2.2 Structure standard 47
F.2.3 Edge structure 48
F.2.4 Wave standard 48

F.3 Fundamentals 49

Annex G (informative) Guidelines for the evaluation of the test value uncertainty 52

G.1 General 52
G.2 Terms and definitions 52
G.3 Test value uncertainty for probing form dispersion errors, u(PForm), and flat-form distortion errors, u(DForm.Pla) 52
G.3.1 General 52
G.3.2 Form deviation of the test artefact, F 52
G.3.3 Standard uncertainty of the form deviation of the reference standard, u(F) 53
G.4 Test value uncertainty of probing size error, u(PSize), distortion error, u(DCC), and length measurement error, u(EVol) 53
G.4.1 General 53
G.4.2 Uncertainty due to the calibration of the reference standard, uCal 54
G.4.3 Uncertainty due to the CTE of the reference standard, uCTE 54
G.4.4 Uncertainty due to the input temperature of the reference standard, ut 55
G.4.5 Uncertainty due to misalignment of the reference standard, uAlign 55
G.4.6 Uncertainty of fixturing the reference standard, uFixt 56
G.4.7 Uncertainty due to form deviation of the balls of the reference standard, uForm 57

Annex H (informative) Relation to the GPS matrix model 59

H.1 General 59
H.2 Information about this document and its use 59
H.3 Position in the GPS matrix model 59
H.4 Related standards 59

Bibliography 60