

# DIN EN ISO 10360-13:2023-11 (E)

## Geometrical product specifications (GPS ) - Acceptance and reverification tests for coordinate measuring systems (CMS) - Part 13: Optical 3D CMS (ISO 10360-13:2021)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		5
Foreword .....		6
Introduction .....		7
<b>1</b>	<b>Scope .....</b>	<b>9</b>
<b>2</b>	<b>Normative references .....</b>	<b>9</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>9</b>
<b>4</b>	<b>Symbols .....</b>	<b>14</b>
<b>5</b>	<b>Rated operating conditions .....</b>	<b>14</b>
5.1	Environmental conditions .....	14
5.2	Operating conditions .....	15
5.2.1	General .....	15
5.2.2	Material and surface characteristic of material standards .....	15
5.2.3	Pre-processing .....	16
<b>6</b>	<b>Acceptance and reverification test .....</b>	<b>16</b>
6.1	General .....	16
6.2	Distortion characteristics .....	16
6.2.1	General .....	16
6.2.2	Distortion error .....	16
6.3	Probing characteristics .....	20
6.3.1	Principle .....	20
6.3.2	Material standard .....	20
6.3.3	Procedure .....	21
6.3.4	Derivation of test results .....	21
6.3.5	Flat-form distortion error .....	22
6.4	Volumetric length measurement error in concatenated measurement volume .....	25
6.4.1	Principle .....	25
6.4.2	Material standard .....	25
6.4.3	Low CTE case .....	25
6.4.4	Procedure .....	26
6.4.5	Derivation of test results .....	28
<b>7</b>	<b>Conformity with the specification .....</b>	<b>28</b>
7.1	Acceptance test .....	28
7.1.1	Acceptance criteria .....	28
7.2	Reverification test .....	30
<b>8</b>	<b>Applications .....</b>	<b>31</b>
8.1	Acceptance test .....	31
8.2	Reverification test .....	31
8.3	Interim check .....	31
<b>9</b>	<b>Indication in product documentation and data sheets .....</b>	<b>31</b>

<b>Annex A (informative) Evaluation of bi-directional length measurement characteristics .....</b>	<b>32</b>
<b>A.1 General .....</b>	<b>32</b>
<b>A.2 Derivation of bi-directional length measurement test results .....</b>	<b>32</b>
<b>A.2.1 General .....</b>	<b>32</b>
<b>A.2.2 Bi-directional length measurement error compounded from test results based on point cloud .....</b>	<b>32</b>
<b>A.3 Indication in product documentation and data sheets .....</b>	<b>33</b>
<b>Annex B (normative) Artefacts that represent a calibrated test length and corresponding measurement procedures .....</b>	<b>34</b>
<b>B.1 General .....</b>	<b>34</b>
<b>B.2 Artefact and procedure for realizing calibrated test length .....</b>	<b>35</b>
<b>B.2.1 General .....</b>	<b>35</b>
<b>B.2.2 Ball plates or ball bars measured in a centre-to-centre manner by point cloud .....</b>	<b>35</b>
<b>B.2.3 Laser interferometry measured in a centre-to-centre manner .....</b>	<b>35</b>
<b>B.2.4 Step gauges measured in a face-to-face manner .....</b>	<b>36</b>
<b>B.2.5 CMM positioning the gauging surface(s) .....</b>	<b>36</b>
<b>Annex C (informative) Procedure of concatenated length measurement to assess the influence of the concatenation path on error .....</b>	<b>37</b>
<b>C.1 General .....</b>	<b>37</b>
<b>C.2 Concatenated length measurement through detoured concatenation pathway .....</b>	<b>37</b>
<b>C.3 Example of detoured concatenation pathway .....</b>	<b>38</b>
<b>Annex D (informative) Alignment of artefacts .....</b>	<b>41</b>
<b>D.1 General .....</b>	<b>41</b>
<b>D.2 Parallel face artefacts .....</b>	<b>41</b>
<b>D.3 Ball bar .....</b>	<b>41</b>
<b>Annex E (informative) Surface characteristic of material standard .....</b>	<b>43</b>
<b>E.1 General .....</b>	<b>43</b>
<b>E.2 Surface characteristics of material standards potentially impacting measuring performance of optical 3D CMS .....</b>	<b>43</b>
<b>E.2.1 Colour .....</b>	<b>43</b>
<b>E.2.2 Glossiness .....</b>	<b>43</b>
<b>E.2.3 Roughness .....</b>	<b>43</b>
<b>E.2.4 Other optical characteristics attributed to surface sublayer .....</b>	<b>44</b>
<b>E.2.5 Evaluation of surface characteristics .....</b>	<b>44</b>
<b>E.3 Potential impact behind surface characteristics restricted in the main text of this document .....</b>	<b>44</b>
<b>E.4 Possible performance evaluation of optical 3D CMS with influence of surface characteristics of material standards .....</b>	<b>44</b>
<b>E.4.1 Usage of optical spectral transmittancy of colour filter to emulate different surface colour .....</b>	<b>44</b>
<b>E.4.2 Usage of equivalent optical attenuation means to emulate different surface colour in cases of monochromatic optical 3D CMS .....</b>	<b>45</b>
<b>E.4.3 Usage of material standards having identical nominal geometries but different intended surface characteristics .....</b>	<b>46</b>
<b>Annex F (informative) Structural resolution test .....</b>	<b>47</b>
<b>F.1 General .....</b>	<b>47</b>
<b>F.2 Test method .....</b>	<b>47</b>
<b>F.2.1 General .....</b>	<b>47</b>
<b>F.2.2 Structure standard .....</b>	<b>47</b>
<b>F.2.3 Edge structure .....</b>	<b>48</b>
<b>F.2.4 Wave standard .....</b>	<b>48</b>

<b>F.3</b>	<b>Fundamentals</b> .....	<b>49</b>
	<b>Annex G (informative) Guidelines for the evaluation of the test value uncertainty</b> .....	<b>52</b>
<b>G.1</b>	<b>General</b> .....	<b>52</b>
<b>G.2</b>	<b>Terms and definitions</b> .....	<b>52</b>
<b>G.3</b>	<b>Test value uncertainty for probing form dispersion errors, <math>u(PForm)</math>, and flat-form distortion errors, <math>u(DForm.Pla)</math></b> .....	<b>52</b>
<b>G.3.1</b>	<b>General</b> .....	<b>52</b>
<b>G.3.2</b>	<b>Form deviation of the test artefact, <math>F</math></b> .....	<b>52</b>
<b>G.3.3</b>	<b>Standard uncertainty of the form deviation of the reference standard, <math>u(F)</math></b> .....	<b>53</b>
<b>G.4</b>	<b>Test value uncertainty of probing size error, <math>u(PSize)</math>, distortion error, <math>u(DCC)</math>, and length measurement error, <math>u(EVol)</math></b> .....	<b>53</b>
<b>G.4.1</b>	<b>General</b> .....	<b>53</b>
<b>G.4.2</b>	<b>Uncertainty due to the calibration of the reference standard, <math>uCal</math></b> .....	<b>54</b>
<b>G.4.3</b>	<b>Uncertainty due to the CTE of the reference standard, <math>uCTE</math></b> .....	<b>54</b>
<b>G.4.4</b>	<b>Uncertainty due to the input temperature of the reference standard, <math>ut</math></b> .....	<b>55</b>
<b>G.4.5</b>	<b>Uncertainty due to misalignment of the reference standard, <math>uAlign</math></b> .....	<b>55</b>
<b>G.4.6</b>	<b>Uncertainty of fixturing the reference standard, <math>uFixt</math></b> .....	<b>56</b>
<b>G.4.7</b>	<b>Uncertainty due to form deviation of the balls of the reference standard, <math>uForm</math></b> .....	<b>57</b>
	<b>Annex H (informative) Relation to the GPS matrix model</b> .....	<b>59</b>
<b>H.1</b>	<b>General</b> .....	<b>59</b>
<b>H.2</b>	<b>Information about this document and its use</b> .....	<b>59</b>
<b>H.3</b>	<b>Position in the GPS matrix model</b> .....	<b>59</b>
<b>H.4</b>	<b>Related standards</b> .....	<b>59</b>
	<b>Bibliography</b> .....	<b>60</b>