

DIN EN ISO 10360-13:2023-11 (E)

Geometrical product specifications (GPS) - Acceptance and reverification tests for coordinate measuring systems (CMS) - Part 13: Optical 3D CMS (ISO 10360-13:2021)

Contents		Page
European foreword		5
Foreword		6
Introduction		7
1	Scope	9
2	Normative references	9
3	Terms and definitions	9
4	Symbols	14
5	Rated operating conditions	14
5.1	Environmental conditions	14
5.2	Operating conditions	15
5.2.1	General	15
5.2.2	Material and surface characteristic of material standards	15
5.2.3	Pre-processing	16
6	Acceptance and reverification test	16
6.1	General	16
6.2	Distortion characteristics	16
6.2.1	General	16
6.2.2	Distortion error	16
6.3	Probing characteristics	20
6.3.1	Principle	20
6.3.2	Material standard	20
6.3.3	Procedure	21
6.3.4	Derivation of test results	21
6.3.5	Flat-form distortion error	22
6.4	Volumetric length measurement error in concatenated measurement volume	25
6.4.1	Principle	25
6.4.2	Material standard	25
6.4.3	Low CTE case	25
6.4.4	Procedure	26
6.4.5	Derivation of test results	28
7	Conformity with the specification	28
7.1	Acceptance test	28
7.1.1	Acceptance criteria	28
7.2	Reverification test	30
8	Applications	31
8.1	Acceptance test	31
8.2	Reverification test	31
8.3	Interim check	31
9	Indication in product documentation and data sheets	31

Annex A (informative) Evaluation of bi-directional length measurement characteristics	32
A.1 General	32
A.2 Derivation of bi-directional length measurement test results	32
A.2.1 General	32
A.2.2 Bi-directional length measurement error compounded from test results based on point cloud	32
A.3 Indication in product documentation and data sheets	33
Annex B (normative) Artefacts that represent a calibrated test length and corresponding measurement procedures	34
B.1 General	34
B.2 Artefact and procedure for realizing calibrated test length	35
B.2.1 General	35
B.2.2 Ball plates or ball bars measured in a centre-to-centre manner by point cloud	35
B.2.3 Laser interferometry measured in a centre-to-centre manner	35
B.2.4 Step gauges measured in a face-to-face manner	36
B.2.5 CMM positioning the gauging surface(s)	36
Annex C (informative) Procedure of concatenated length measurement to assess the influence of the concatenation path on error	37
C.1 General	37
C.2 Concatenated length measurement through detoured concatenation pathway	37
C.3 Example of detoured concatenation pathway	38
Annex D (informative) Alignment of artefacts	41
D.1 General	41
D.2 Parallel face artefacts	41
D.3 Ball bar	41
Annex E (informative) Surface characteristic of material standard	43
E.1 General	43
E.2 Surface characteristics of material standards potentially impacting measuring performance of optical 3D CMS	43
E.2.1 Colour	43
E.2.2 Glossiness	43
E.2.3 Roughness	43
E.2.4 Other optical characteristics attributed to surface sublayer	44
E.2.5 Evaluation of surface characteristics	44
E.3 Potential impact behind surface characteristics restricted in the main text of this document	44
E.4 Possible performance evaluation of optical 3D CMS with influence of surface characteristics of material standards	44
E.4.1 Usage of optical spectral transmittancy of colour filter to emulate different surface colour	44
E.4.2 Usage of equivalent optical attenuation means to emulate different surface colour in cases of monochromatic optical 3D CMS	45
E.4.3 Usage of material standards having identical nominal geometries but different intended surface characteristics	46
Annex F (informative) Structural resolution test	47
F.1 General	47
F.2 Test method	47
F.2.1 General	47
F.2.2 Structure standard	47
F.2.3 Edge structure	48
F.2.4 Wave standard	48

F.3	Fundamentals	49
	Annex G (informative) Guidelines for the evaluation of the test value uncertainty	52
G.1	General	52
G.2	Terms and definitions	52
G.3	Test value uncertainty for probing form dispersion errors, $u(PForm)$, and flat-form distortion errors, $u(DForm.Pla)$	52
G.3.1	General	52
G.3.2	Form deviation of the test artefact, F	52
G.3.3	Standard uncertainty of the form deviation of the reference standard, $u(F)$	53
G.4	Test value uncertainty of probing size error, $u(PSize)$, distortion error, $u(DCC)$, and length measurement error, $u(EVol)$	53
G.4.1	General	53
G.4.2	Uncertainty due to the calibration of the reference standard, $uCal$	54
G.4.3	Uncertainty due to the CTE of the reference standard, $uCTE$	54
G.4.4	Uncertainty due to the input temperature of the reference standard, ut	55
G.4.5	Uncertainty due to misalignment of the reference standard, $uAlign$	55
G.4.6	Uncertainty of fixturing the reference standard, $uFixt$	56
G.4.7	Uncertainty due to form deviation of the balls of the reference standard, $uForm$	57
	Annex H (informative) Relation to the GPS matrix model	59
H.1	General	59
H.2	Information about this document and its use	59
H.3	Position in the GPS matrix model	59
H.4	Related standards	59
	Bibliography	60