

ISO 21920-3:2021-12 (E)

Geometrical product specifications (GPS) - Surface texture: Profile - Part 3: Specification operators

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Complete specification operator	2
4.1 Introduction	2
4.2 General	2
4.3 General default settings	2
4.4 Default settings based on the specification	3
4.4.1 General rules	3
4.4.2 Default settings based on N_{ic} or Scn	4
4.4.3 Default settings for Ra, Rq, Rz, Rp, Rv, Rzx and Rt based on the upper tolerance limit	5
4.4.4 Default settings for Ra, Rq, Rz, Rp, Rv, Rzx and Rt based on bilateral tolerance limits	6
4.4.5 Default settings for Ra, Rq, Rz, Rp, Rv, Rzx and Rt based on the lower tolerance limit	7
4.4.6 Default settings for Pt	7
5 Default attribute values for parameters from ISO 21920-2	8
5.1 General	8
5.2 Default attribute values for height parameters and spatial parameters	8
5.3 Default attribute values for material ratio functions and related parameters	8
5.4 Default attribute values for volume parameters	9
5.5 Default attribute values for feature parameters	9
6 Default units for parameters from ISO 21920-2	9
6.1 General	9
6.2 Height parameters	10
6.3 Spatial parameters	10
6.4 Hybrid parameters	10
6.5 Material ratio functions and related parameters	10
6.6 Volume parameters	11
6.7 Feature parameters	11
Annex A (informative) How to determine specification operators	13
Annex B (informative) Examples of the determination of default settings	15
Annex C (informative) Major changes from ISO 4288	23
Annex D (informative) Settings for profile surface texture evaluation in the absence of a specification	24
Annex E (informative) Overview of profile and areal standards in the GPS matrix model	27
Annex F (informative) Relation with the GPS matrix	28
Bibliography	29