

DIN EN ISO 5167-5:2023-08 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 5: Cone meters (ISO 5167-5:2022)

Contents		Page
European foreword		3
Foreword		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and definitions		6
4 Principles of the method of measurement and computation		7
5 Cone meters		8
5.1 Field of application		8
5.2 General shape		8
5.3 Material and manufacture		12
5.4 Pressure tapplings		13
5.5 Discharge coefficient, C		13
5.5.1 Limits of use		13
5.5.2 Discharge coefficient of the cone meter		13
5.6 Expansibility (expansion) factor, ε		14
5.7 Uncertainty of the discharge coefficient, C		14
5.8 Uncertainty of the expansibility (expansion) factor, ε		14
5.9 Pressure loss		14
6 Installation requirements		15
6.1 General		15
6.2 Minimum upstream and downstream straight lengths for installations between various fittings and the cone meter		15
6.2.1 General		15
6.2.2 Single 90° bend		16
6.2.3 Two 90° bends in perpendicular planes		16
6.2.4 Concentric expander		16
6.2.5 Partially closed valves		16
6.3 Additional specific installation requirements for cone meters		16
6.3.1 Circularity and cylindricality of the pipe		16
6.3.2 Roughness of the upstream and downstream pipe		16
6.3.3 Positioning of a thermowell		16
7 Flow calibration of cone meters		17
7.1 General		17
7.2 Test facility		17
7.3 Meter installation		17
7.4 Design of the test programme		17
7.5 Reporting the calibration results		18
7.6 Uncertainty analysis of the calibration		18
7.6.1 General		18
7.6.2 Uncertainty of the test facility		18
7.6.3 Uncertainty of the discharge coefficient of the cone meter		18
Annex A (informative) Table of expansibility (expansion) factor		19
Bibliography		20