

ISO 5167-1:2022-06 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 1: General principles and requirements

| Contents | | Page |
|-------------------|--|-------------|
| Foreword..... | | v |
| Introduction..... | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 3.1 | Pressure measurement..... | 2 |
| 3.2 | Primary devices..... | 2 |
| 3.3 | Flow..... | 3 |
| 4 | Symbols and subscripts | 6 |
| 4.1 | Symbols..... | 6 |
| 5 | Principle of the method of measurement and computation | 7 |
| 5.1 | Principle of the method of measurement..... | 7 |
| 5.2 | Method of determination of the required diameter ratio for the selected standard primary device..... | 8 |
| 5.3 | Computation of flow rate..... | 8 |
| 5.4 | Determination of density, pressure and temperature..... | 8 |
| 5.4.1 | General..... | 8 |
| 5.4.2 | Density..... | 9 |
| 5.4.3 | Static pressure..... | 9 |
| 5.4.4 | Temperature..... | 9 |
| 5.5 | Differential pressure flow measurement system..... | 10 |
| 5.5.1 | General..... | 10 |
| 5.5.2 | Primary device..... | 11 |
| 5.5.3 | Impulse lines and transmitters..... | 12 |
| 5.5.4 | Impulse line isolation valves and valve manifolds..... | 12 |
| 5.5.5 | Flow computer..... | 12 |
| 5.6 | Differential pressure flow measurement system design considerations..... | 12 |
| 5.6.1 | Flow rate turndown and stacked transmitters..... | 12 |
| 5.6.2 | Meter calibration..... | 12 |
| 5.6.3 | Permanent pressure loss..... | 13 |
| 5.6.4 | Diagnostics and meter verification..... | 14 |
| 5.6.5 | Overall uncertainty of differential pressure metering system..... | 14 |
| 6 | General requirements for the measurements | 14 |
| 6.1 | Primary device..... | 14 |
| 6.2 | Nature of the fluid..... | 15 |
| 6.3 | Flow conditions..... | 15 |
| 7 | Installation requirements | 15 |
| 7.1 | General..... | 15 |
| 7.2 | Minimum upstream and downstream straight lengths..... | 17 |
| 7.3 | General requirement for flow conditions at the primary device..... | 17 |
| 7.3.1 | Requirement..... | 17 |
| 7.3.2 | Swirl-free conditions..... | 17 |
| 7.3.3 | Good velocity profile conditions..... | 17 |
| 7.4 | Flow conditioners..... | 17 |
| 7.4.1 | Compliance testing..... | 17 |
| 7.4.2 | Specific test..... | 20 |

| | | |
|---------------------|---|-----------|
| 8 | Uncertainties on the measurement of flow rate | 20 |
| 8.1 | General..... | 20 |
| 8.2 | Definition of uncertainty..... | 20 |
| 8.3 | Practical computation of the uncertainty..... | 21 |
| | 8.3.1 Component uncertainties..... | 21 |
| | 8.3.2 Practical working formula..... | 21 |
| Annex A | (informative) Iterative computations | 24 |
| Annex B | (informative) Examples of values of the pipe wall uniform equivalent roughness, k_a | 26 |
| Annex C | (informative) Flow conditioners and flow straighteners | 27 |
| Annex D | (informative) Differential pressure transmitters, flow range and turndown | 29 |
| Annex E | (informative) Example of uncertainty calculation for a differential pressure device | 36 |
| Annex F | (informative) Permanent pressure loss example | 40 |
| Bibliography | | 42 |