ISO 5167-2:2022-06 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 2: Orifice plates

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms, definitions and symbols **1**

4 Principles of the method of measurement and computation **2**

5 Orifice plates **2**

5.1 Description 2

5.1.1 General 2

5.1.2 General shape 2

5.1.3 Upstream face A 3

5.1.4 Downstream face B 4

5.1.5 Thicknesses E and e 4

5.1.6 Angle of bevel, α 5

5.1.7 Edges G, H and I 5

5.1.8 Diameter of orifice, d 5

5.1.9 Bidirectional plates 6

5.1.10 Material and manufacture 6

5.2 Pressure tappings 6

5.2.1 General 6

5.2.2 Orifice plate with D and $D/2$ tappings or flange tappings 6

5.2.3 Orifice plate with corner tappings 8

5.3 Coefficients and corresponding uncertainties of orifice plates 11

5.3.1 Limits of use 11

5.3.2 Coefficients 12

5.3.3 Uncertainties 13

5.4 Pressure loss, $\Delta\varpi$ 14

6 Installation requirements **15**

6.1 General 15

6.2 Minimum upstream and downstream straight lengths for installation between various fittings and the orifice plate 16

6.3 Flow conditioners 21

6.3.1 General 21

6.3.2 19-tube bundle flow straightener (1998) 21

6.3.3 The Zanker flow conditioner plate 27

6.4 Circularity and cylindricality of the pipe 28

6.5 Location of orifice plate and carrier rings 29

6.6 Method of fixing and gaskets 30

7 Flow calibration of orifice meters **30**

7.1 General 30

7.2 Test facility 31

7.3 Meter installation 31

7.4 Design of the test programme 31

7.5 Reporting the calibration results 31

7.6 Uncertainty analysis of the calibration 32

7.6.1 General 32

7.6.2 Uncertainty of the test facility 32

7.6.3 Uncertainty of the orifice meter 32

Annex A (informative) **Tables of discharge coefficients and expansibility [expansion] factors** **33**

Annex B (informative) **Flow conditioners** **47**

Bibliography **52**