

ISO 5167-6:2022-10 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 6: Wedge meters

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principles of the method of measurement and computation | 2 |
| 5 | Wedge meters | 3 |
| 5.1 | Field of application | 3 |
| 5.2 | General shape | 4 |
| 5.3 | Material and manufacture | 5 |
| 5.4 | Pressure tapplings | 5 |
| 5.5 | Discharge coefficient, C | 6 |
| 5.5.1 | Limits of use | 6 |
| 5.5.2 | Discharge coefficient of the wedge meter | 6 |
| 5.6 | Expansibility [expansion] factor, | 6 |
| 5.7 | Uncertainty of the discharge coefficient, C | 7 |
| 5.8 | Uncertainty of the expansibility [expansion] factor, | 7 |
| 5.9 | Pressure loss | 7 |
| 6 | Installation requirements | 7 |
| 6.1 | General | 7 |
| 6.2 | Minimum upstream and downstream straight lengths for installations between various fittings and the wedge meter | 7 |
| 6.3 | Additional specific installation requirements for wedge meters | 8 |
| 6.3.1 | Circularity and cylindricality of the pipe | 8 |
| 6.3.2 | Roughness of the upstream and downstream pipe | 8 |
| 6.3.3 | Positioning of a thermowell | 8 |
| 6.3.4 | Bidirectional wedge meters | 9 |
| 7 | Flow calibration of wedge meters | 9 |
| 7.1 | General | 9 |
| 7.2 | Test facility | 9 |
| 7.3 | Meter installation | 9 |
| 7.4 | Design of the test programme | 9 |
| 7.5 | Reporting the calibration results | 10 |
| 7.6 | Uncertainty analysis of the calibration | 10 |
| 7.6.1 | General | 10 |
| 7.6.2 | Uncertainty of the test facility | 10 |
| 7.6.3 | Uncertainty of the discharge coefficient of the wedge meter | 10 |
| Annex A (informative) | Table of expansibility [expansion] factor | 11 |
| Annex B (informative) | Use of Kd2 parameter | 12 |
| Bibliography | | 13 |