ISO 5167-5:2022-10 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 5: Cone meters

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Principles of the method of measurement and computation 2

5 Cone meters 3
5.1 Field of application 3
5.2 General shape 3
5.3 Material and manufacture 7
5.4 Pressure tappings 8
5.5 Discharge coefficient, C 8
5.5.1 Limits of use 8
5.5.2 Discharge coefficient of the cone meter 8
5.6 Expansibility (expansion) factor, ... 9
5.7 Uncertainty of the discharge coefficient, C 9
5.8 Uncertainty of the expansibility (expansion) factor, ... 9
5.9 Pressure loss 9

6 Installation requirements 10
6.1 General 10
6.2 Minimum upstream and downstream straight lengths for installations between various fittings and the cone meter 10
6.2.1 General 10
6.2.2 Single 90° bend 11
6.2.3 Two 90° bends in perpendicular planes 11
6.2.4 Concentric expander 11
6.2.5 Partially closed valves 11
6.3 Additional specific installation requirements for cone meters 11
6.3.1 Circularity and cylindricality of the pipe 11
6.3.2 Roughness of the upstream and downstream pipe 11
6.3.3 Positioning of a thermowell 11

7 Flow calibration of cone meters 12
7.1 General 12
7.2 Test facility 12
7.3 Meter installation 12
7.4 Design of the test programme 12
7.5 Reporting the calibration results 13
7.6 Uncertainty analysis of the calibration 13
7.6.1 General 13
7.6.2 Uncertainty of the test facility 13
7.6.3 Uncertainty of the discharge coefficient of the cone meter 13

Annex A (informative) Table of expansibility (expansion) factor 14

Bibliography 15