

# ISO/TR 12767:2023-09 (E)

## Measurement of fluid flow by means of pressure differential devices - Guidelines on the effect of departure from the specifications and operating conditions given in ISO 5167

| <b>Contents</b>     |   | <b>Page</b> |
|---------------------|---|-------------|
| <b>Foreword</b>     |   | <b>v</b>    |
| <b>Introduction</b> |   | <b>vi</b>   |
| <b>1</b>            | <b>Scope</b>  | <b>1</b>    |
| <b>2</b>            | <b>Normative references</b>                                   | <b>1</b>    |
| <b>3</b>            | <b>Terms and definitions</b>                                  | <b>1</b>    |
| <b>4</b>            | <b>Symbols</b>  | <b>2</b>    |
| <b>5</b>            | <b>Effect of errors on flowrate calculations</b>              | <b>3</b>    |
| 5.1                 | General   | 3           |
| 5.2                 | Quantifiable effects  | 3           |
| <b>6</b>            | <b>Effects of deviations in construction</b>                  | <b>3</b>    |
| 6.1                 | Orifice-plate edge sharpness                                  | 3           |
| 6.2                 | Thickness of orifice edge                                     | 4           |
| 6.3                 | Condition of upstream and downstream faces of orifice plate   | 5           |
| 6.4                 | Position of pressure tapplings for an orifice                 | 6           |
| 6.4.1               | General   | 6           |
| 6.4.2               | Calculation of discharge coefficient                          | 6           |
| 6.4.3               | Estimation of additional uncertainty                          | 6           |
| 6.4.4               | Example   | 6           |
| 6.5                 | Condition of pressure tapplings                               | 7           |
| <b>7</b>            | <b>Effects of pipeline near the meter</b>                     | <b>7</b>    |
| 7.1                 | Pipe diameter   | 7           |
| 7.2                 | Steps and taper sections                                      | 7           |
| 7.3                 | Diameter of carrier ring                                      | 8           |
| 7.4                 | Undersize joint rings   | 11          |
| 7.5                 | Protruding welds  | 11          |
| 7.6                 | Eccentricity  | 11          |
| <b>8</b>            | <b>Effects of pipe layout</b>                                 | <b>13</b>   |
| 8.1                 | General   | 13          |
| 8.2                 | Discharge coefficient compensation                            | 14          |
| 8.2.1               | Corrections   | 14          |
| 8.2.2               | Additional uncertainty  | 15          |
| 8.3                 | Pressure tapplings  | 16          |
| 8.4                 | Devices for improving flow conditions                         | 16          |
| <b>9</b>            | <b>Operational deviations</b>                                 | <b>16</b>   |
| 9.1                 | General   | 16          |
| 9.2                 | Deformation of an orifice plate                               | 17          |
| 9.2.1               | General   | 17          |
| 9.2.2               | Elastic deformation   | 17          |
| 9.2.3               | Plastic deformation   | 17          |
| 9.3                 | Deposition on the upstream face of an orifice plate           | 18          |
| 9.4                 | Deposition in the meter tube                                  | 22          |
| 9.5                 | Orifice-plate edge sharpness                                  | 23          |
| 9.5.1               | Deterioration   | 23          |
| 9.5.2               | Plate reversal  | 23          |
| 9.6                 | Deposition and increase of surface roughness in Venturi tubes | 24          |

|           |                                |           |
|-----------|--------------------------------|-----------|
| 9.6.1     | General                        | 24        |
| 9.6.2     | Deposition                     | 24        |
| 9.6.3     | Surface roughness              | 24        |
| <b>10</b> | <b>Pipe roughness</b>          | <b>25</b> |
| 10.1      | General                        | 25        |
| 10.2      | Upstream pipe                  | 26        |
| 10.3      | Downstream pipe                | 30        |
| 10.4      | Reduction of roughness effects | 30        |
| 10.5      | Maintenance                    | 30        |
|           | <b>Bibliography</b>            | <b>32</b> |