

ISO 24062:2023-12 (E)

Measurement of fluid flow in closed conduits - Clamp-on ultrasonic transit-time meters for liquids and gases

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
3.1	Quantities.....	1
3.2	Meter design.....	2
3.3	Thermodynamic conditions.....	2
3.4	Statistics.....	3
3.5	Calibration.....	4
3.6	Symbols and subscripts.....	4
4	Principle of measurement	5
4.1	General.....	5
4.2	Generic description.....	6
4.2.1	Transducers.....	7
4.2.2	Ultrasonic path configurations.....	8
4.2.3	Electronic unit functionality.....	9
4.3	Special considerations.....	10
4.3.1	Gas.....	10
4.3.2	Extreme temperatures.....	10
4.4	Additional measurements.....	10
4.4.1	Standard volume flow.....	10
4.4.2	Heat flow.....	11
4.4.3	Mass flow.....	11
5	Test and calibration	11
5.1	General.....	11
5.2	Individual testing — Flow calibration under flowing conditions.....	11
5.2.1	General.....	11
5.2.2	Laboratory flow calibration.....	12
6	Installation	13
6.1	General.....	13
6.2	Installation location.....	13
6.2.1	Upstream and downstream straight pipe length requirements and path configuration.....	13
6.3	Transmitter programming.....	14
6.4	Pressure and temperature inputs.....	14
6.5	Transducer installation.....	15
6.5.1	Transducer type.....	15
6.5.2	Transducer orientation.....	15
6.5.3	Coupling.....	15
6.5.4	Transducer mounting.....	15
6.6	Gas considerations.....	17
6.7	Cable.....	17
6.8	Additional installation effects.....	18
6.8.1	Non-steady flow.....	18
6.8.2	Contamination by secondary phase.....	18
6.8.3	Vibration.....	18
6.8.4	Thermal insulation.....	18

6.8.5	Stratification	19
6.8.6	Wall roughness signal considerations	19
6.8.7	Non-Newtonian fluids	19
6.9	Operational diagnostics	19
6.9.1	Fluid speed of sound	19
6.9.2	Gain	20
6.9.3	Signal to noise ratio	20
7	Maintenance	20
8	Uncertainty in measurement	20
8.1	General	20
8.2	Mathematical model	21
8.3	Evaluation of the contributory variances	22
8.3.1	Uncertainty of the cross-sectional area, $u(A)$	22
8.3.2	Uncertainty in the velocity profile, $u(K_p)$	23
8.3.3	Uncertainty of the path-geometry factor, $u(K_g)$ and time measurement	24
8.3.4	Uncertainty of time measurement	24
8.3.5	Uncertainty of the delay time, $u(t_0)$	24
8.3.6	Effect of multiple paths	24
8.4	Additional effects on measurement uncertainty	25
8.4.1	Effect of pipe material on sound speed	25
8.4.2	Effect of fluid sound speed	25
8.4.3	Reproducibility of transmitter mounting	25
8.4.4	External influences	25
	Annex A (informative) Example of uncertainty calculation	26
	Bibliography	33