

ISO 3966:2025-07 (E)

Measurement of fluid flow in closed conduits - Velocity area method using Pitot static tubes

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms, definitions and symbols	1
3.1	Terms and definitions	1
3.2	Symbols	2
4	Principle	3
4.1	General principle	3
4.1.1	Graphical integration of the velocity area (see Clause 9)	4
4.1.2	Numerical integration of the velocity area (see Clause 10)	4
4.1.3	Arithmetical methods (see Clause 11)	4
4.2	Measurement of the measuring cross-section	4
4.2.1	Circular cross-sections	4
4.2.2	Rectangular cross-sections	4
4.3	Measurement of local velocities	5
4.3.1	Method of exploring traverse section	5
4.3.2	Reference measurement	5
4.3.3	Checking of velocity distribution	5
4.4	Location and number of measuring points in the cross-section	6
4.4.1	General requirements	6
4.4.2	Circular cross-sections	6
4.4.3	Rectangular cross-sections	6
5	Design of Pitot tubes	6
5.1	General description	6
5.2	Criteria to be fulfilled by the Pitot tube	7
6	Requirements for use of Pitot tubes	8
6.1	Selection of the measuring cross-section	8
6.1.1	Location of the measuring cross-section (of selection)	8
6.1.2	Avoidance of asymmetry, swirl and turbulences	8
6.1.3	Maximum flow deviation	8
6.1.4	Measuring cross-sectional velocity distribution	8
6.1.5	Measuring cross-sectional temperature distribution	10
6.1.6	Preliminary traverse tests	10
6.2	Devices for improving flow conditions	10
6.2.1	Anti-swirl device	10
6.2.2	Profile developer	12
6.2.3	Turning vanes	13
6.2.4	Static mixer	14
6.2.5	Positioning/Location of devices	16
6.2.6	Provisional guiding installation	16
6.3	Limits of use	16
6.3.1	Nature of the fluid	16
6.3.2	Range of velocities	16
6.3.3	Nature of the flow	17
6.3.4	Dimensional limitations	17

6.3.5	Influence of turbulence	17
6.4	Performance of measurements	17
6.4.1	Measurement of differential pressure	17
6.4.2	Differential pressure fluctuations	17
6.4.3	Determination of fluid density	18
6.5	Inspection and maintenance of the Pitot tube	18
7	Positioning of Pitot tube	18
8	Velocity computation	18
8.1	Verification of conditions for a measurement	18
8.2	Formulae for velocity computation	19
9	Determination of the discharge velocity by graphical integration of the velocity area	21
9.1	Circular cross-section	21
9.2	Rectangular cross-sections	23
10	Determination of the discharge velocity by numerical integration of the velocity area	24
10.1	Circular cross-sections	25
10.2	Rectangular cross-sections	27
11	Determination of the discharge velocity by arithmetic methods	27
11.1	"Log-linear" method	28
11.1.1	Circular cross-sections	28
11.1.2	Rectangular cross-sections	28
11.2	Log-Chebyshev method	29
11.2.1	Circular cross-sections	29
11.2.2	Rectangular cross-sections	30
12	Corrections of local velocity measurements	31
12.1	Correction for stem blockage	31
12.1.1	Case where the correction can be neglected	31
12.1.2	Estimation of the correction of local velocity measurement	31
12.1.3	Estimation of the overall correction of the flow-rate value (application to arithmetic methods)	32
12.2	Correction for transverse velocity gradient	33
12.2.1	Correction for measuring point position	34
12.2.2	Overall correction of flow rate	34
12.3	Correction for turbulence	35
12.4	Correction for head loss	36
13	Errors	36
13.1	Definition of the error	36
13.2	Errors in the estimation of the local velocity	36
13.2.1	Random errors	36
13.2.2	Systematic errors	37
13.3	Errors in the estimation of flow rate	38
13.3.1	Random errors	38
13.3.2	Systematic errors	38
13.4	Definition of the standard uncertainty	39
13.5	Definition of the expanded uncertainty	39
13.6	Calculation of standard uncertainty	40
13.6.1	Standard uncertainty on local velocity measurement	40
13.6.2	Standard uncertainty on flow-rate measurement	41
Annex A (normative)	Pitot tubes	42
Annex B (normative)	Correction to the measuring position of Pitot tubes used in a transverse velocity gradient	48
Annex C (normative)	Study concerning turbulence correction	50

Annex D (normative) Damping of pressure gauges	53
Annex E (normative) Measurements with a Pitot tube in a compressible fluid	55
Annex F (normative) Determination of coefficient m for extrapolation near the wall	59
Annex G (informative) Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes	60
Bibliography	63