ISO 5167-1:2003-03 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 1: General prin ciples and requirements

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and subscripts 6
4.1 Symbols 6
4.2 Subscripts 7

5 Principle of the method of measurement and computation 7
5.1 Principle of the method of measurement 7
5.2 Method of determination of the diameter ratio of the selected standard primary device 8
5.3 Computation of flowrate 8
5.4 Determination of density, pressure and temperature 8

6 General requirements for the measurements 10
6.1 Primary device 10
6.2 Nature of the fluid 11
6.3 Flow conditions 11

7 Installation requirements 11
7.1 General 11
7.2 Minimum upstream and downstream straight lengths 13
7.3 General requirement for flow conditions at the primary device 13
7.4 Flow conditioners (see also Annex C) 13

8 Uncertainties on the measurement of flowrate 16
8.1 Definition of uncertainty 16
8.2 Practical computation of the uncertainty 17

Annex A (informative) Iterative computations 19

Annex B (informative) Examples of values of the pipe wall uniform equivalent roughness, k 21

Annex C (informative) Flow conditioners and flow straighteners 22

Bibliography 33