ISO 9300:2005-08 (E)

Measurement of gas flow by means of critical flow Venturi nozzles

Contents

Page

Foreword iv

1 Scope 1

2 Terms and definitions 1
2.1 Pressure measurement 1
2.2 Temperature measurement 2
2.3 Venturi nozzles 2
2.4 Flow 2

3 Symbols 5

4 Basic equations 6
4.1 State equation 6
4.2 Flow-rate under ideal conditions 6
4.3 Flow-rate under real conditions 6
4.4 Critical mass flux 7

5 Applications for which the method is suitable 7

6 Standard critical flow Venturi nozzles (CFVN) 7
6.1 General requirements 7
6.2 Design 8

7 Installation requirements 11
7.1 General 11
7.2 Upstream pipeline 11
7.3 Large upstream space 12
7.4 Downstream requirements 12
7.5 Pressure measurement 12
7.6 Drain holes 13
7.7 Temperature measurement 13
7.8 Density measurement 13
7.9 Calculated density 14

8 Calculation methods 14
8.1 Mass flow-rate 14
8.2 Discharge coefficient, Cd 14
8.3 Critical flow function, C, and real gas critical flow coefficient, CR 15
8.4 Conversion of measured pressure and temperature to stagnation conditions 15
8.5 Maximum permissible downstream pressure 16

9 Uncertainties in the measurement of flow-rate 17
9.1 General 17
9.2 Practical computation of uncertainty 18

Annex A (normative) Venturi nozzle discharge coefficients 19

Annex B (normative) Tables of values for critical flow function C -- Various gases 21

Annex C (normative) Computation of critical mass flux for natural gas mixtures 28

Annex D (normative) Mass flow correction factor for atmospheric air 32

Annex E (normative) Computation of critical mass flux for critical flow nozzles with high nozzle throat to upstream pipe diameter ratio, > 0,25 33

Bibliography 36