ISO/TR 4191:2014-01 (E)

Plastics piping systems for water supply - Unplasticized poly(vinyl chloride)(PVC-U) and oriented PVC-U (PVC-O) - Guida nce for installation

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions,symbols,andabbreviations 2
3.1 Terms and definitions 2
3.2 Symbols 4
3.3 Abbreviations 4

4 Parametersinfluencingdesign 5
4.1 Allowable operating pressure 5
4.2 Ring stiffness of pipes 5

5 Hydraulic properties 7
5.1 Loss of head 7

6 Assemblymethods 9
6.1 General 9
6.2 Integral rubber ring joints 13
6.3 Solvent cement joints 14
6.4 Mechanical joints 15

7 Storage,handling,andtransportofpipes 15
7.1 Handling 15
7.2 Transport 16
7.3 Storage 16
7.4 Cold bending on site 17
7.5 Anchoring and thrust blocks 19

8 Storage,handling,andtransportoffittings,valves,andancillaries 21
8.1 PVC-U fittings, valves, and ancillaries are light and easy to handle 21

9 Installation 22
9.1 Installation below ground 22
9.2 Pipe deflection 25
9.3 Installation above ground 27
9.4 Installation in ducts 31

10 Commissioningbysitepressuretesting 31
10.1 General 31
10.2 Preparation for test 31
10.3 Test pressures 35
10.4 Applying the test 35
10.5 Interpretation of results 36

11 Contaminated soil 36

12 Corrosion protection of metal parts 36
13 Pressure surge 37
14 Usage at lower temperature 37
15 Fatigue 37
16 Repairs 38
17 Pipeline detection 39
Annex A (informative)Classificationofsoils 40
Bibliography 44