

ISO/TR 4191:2014-01 (E)

Plastics piping systems for water supply - Unplasticized poly(vinyl chloride)(PVC-U) and oriented PVC-U (PVC-O) - Guida nce for installation

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions, symbols, and abbreviations	2
3.1	Terms and definitions	2
3.2	Symbols	4
3.3	Abbreviations	4
4	Parameters influencing design	5
4.1	Allowable operating pressure	5
4.2	Ring stiffness of pipes	5
5	Hydraulic properties	7
5.1	Loss of head	7
6	Assembly methods	9
6.1	General	9
6.2	Integral rubber ring joints	13
6.3	Solvent cement joints	14
6.4	Mechanical joints	15
7	Storage, handling, and transport of pipes	15
7.1	Handling	15
7.2	Transport	16
7.3	Storage	16
7.4	Cold bending on site	17
7.5	Anchoring and thrust blocks	19
8	Storage, handling, and transport of fittings, valves, and ancillaries	21
8.1	PVC-U fittings, valves, and ancillaries are light and easy to handle	21
9	Installation	22
9.1	Installation below ground	22
9.2	Pipe deflection	25
9.3	Installation above ground	27
9.4	Installation in ducts	31
10	Commissioning by site pressure testing	31
10.1	General	31
10.2	Preparation for test	31
10.3	Test pressures	35
10.4	Applying the test	35
10.5	Interpretation of results	36
11	Contaminated soil	36

12	Corrosion protection of metal parts	36
13	Pressure surge	37
14	Usage at lower temperature	37
15	Fatigue	37
16	Repairs	38
17	Pipeline detection	39
	Annex A (informative)Classificationofsoils	40
	Bibliography	44