

ISO/TS 16422-3:2023-06 (E)

Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure - Part 3: Fittings

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols	3
5 Material	5
5.1 General.....	5
5.2 Density.....	5
5.3 Orientation factor.....	5
6 General characteristics	5
6.1 Appearance.....	5
6.2 Colour.....	5
6.3 Opacity.....	6
6.4 Classification of fittings.....	6
7 Geometrical characteristics	6
7.1 Design lengths, bend radii and angles.....	6
7.2 Measurement of dimensions.....	6
7.3 Nominal outside diameters and wall thickness.....	6
7.4 Fittings with integral sockets with elastomeric sealing ring type.....	6
8 Pressure and operating temperature	7
8.1 Selection of nominal pressure for water up to and including 25 °C.....	7
8.2 Determination of the allowable operating pressure for water up to 45 °C.....	7
9 Mechanical characteristics — Resistance to hydrostatic pressure	7
10 Physical characteristics	7
11 Sealing rings	8
12 Performance requirements	8
13 Marking	8
13.1 General.....	8
13.2 Minimum required marking.....	8
13.3 Additional marking.....	9
Annex A (normative) Determination of long-term hydrostatic strength	10
Annex B (normative) Determination of circumferential orientation factor	12
Annex C (informative) Recommended dimensions of PVC-O fittings	14
Bibliography	19