

ISO/TR 27925:2023-07 (E)

Carbon dioxide capture, transportation and geological storage - Cross cutting issues - Flow assurance

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 2 |
| 5 | Overview of the necessity of flow assurance in CCS projects | 3 |
| 5.1 | General | 3 |
| 5.2 | Reasons to maintain flow assurance | 3 |
| 5.3 | Potential factors affecting flow of CO₂ streams at individual components of CCS projects | 4 |
| 5.3.1 | General | 4 |
| 5.3.2 | CO₂ sources | 5 |
| 5.3.3 | Capture facilities | 5 |
| 5.3.4 | Transportation | 5 |
| 5.3.5 | Field distribution | 5 |
| 5.3.6 | Injection wells | 6 |
| 5.3.7 | Storage reservoirs | 6 |
| 5.3.8 | Optional components | 7 |
| 5.4 | Providing flow assurance | 7 |
| 5.4.1 | General | 7 |
| 5.4.2 | Technical design | 7 |
| 5.4.3 | Operational procedures and work-flows | 7 |
| 5.4.4 | Overarching project management | 8 |
| 6 | Fluid composition and physical properties | 8 |
| 6.1 | General | 8 |
| 6.2 | CO₂ phase behaviour and thermophysical properties -- Key features | 9 |
| 6.3 | Modelling properties of pure CO₂ | 12 |
| 6.4 | Properties of impure CO₂ -- Phenomena and their modelling | 13 |
| 6.5 | Individual impurities | 16 |
| 6.5.1 | General | 16 |
| 6.5.2 | Water | 16 |
| 6.5.3 | Nitrogen and argon | 16 |
| 6.5.4 | Hydrogen | 16 |
| 6.5.5 | Oxygen | 17 |
| 6.5.6 | Carbon monoxide | 17 |
| 6.5.7 | Methane and ethane | 17 |
| 6.5.8 | Propane and other aliphatic hydrocarbons | 17 |
| 6.5.9 | Nitrogen and sulfur oxides | 17 |
| 6.5.10 | Hydrogen sulfide | 18 |
| 6.5.11 | Carbonyl sulfide | 18 |
| 6.5.12 | Ammonia | 18 |
| 6.5.13 | Amines | 18 |
| 6.5.14 | Benzene, toluene, ethylxylene and xylene | 18 |

| | | |
|--------|---|----|
| 6.5.15 | Methanol | 18 |
| 6.5.16 | Ash, dust, metals and other particulate matter | 19 |
| 6.5.17 | Naphthalene | 19 |
| 6.5.18 | Volatile organic compounds | 19 |
| 6.5.19 | Chlorine | 19 |
| 6.5.20 | Hydrogen chloride, hydrogen fluoride and hydrogen cyanide | 19 |
| 6.5.21 | Glycols | 19 |
| 6.6 | Effects of reactive impurities -- Phenomena and their modelling | 20 |
| 6.6.1 | General | 20 |
| 6.6.2 | Formation of corrosive aqueous phases | 20 |
| 6.6.3 | CO2 specifications | 22 |
| 6.6.4 | Modelling of formation of corrosive aqueous phases | 22 |
| 6.6.5 | Depressurisation and impact of reactive impurities | 23 |
| 6.6.6 | Corrosion issues in CO2 injection wells | 23 |
| 6.6.7 | Monitoring reactive impurities in the CO2 stream | 23 |
| 6.6.8 | Particle, wear and clogging | 24 |
| 6.7 | Modelling of CO2 stream properties in commercial flow assurance tools | 24 |
| 6.7.1 | General | 24 |
| 6.7.2 | Joule-Thomson effect | 25 |
| 6.7.3 | Viscosity | 26 |
| 6.7.4 | Flow assurance simulation for CO2 transportation in pipes | 28 |
| 7 | CO2 pipeline transport and well injection | 29 |
| 7.1 | Operation under single-phase flow conditions | 30 |
| 7.1.1 | General | 30 |
| 7.1.2 | Fluid hammer | 31 |
| 7.1.3 | Shut-down of pipeline and well | 31 |
| 7.1.4 | Start-up and restart of pipeline transport and well injection | 32 |
| 7.2 | Normal operation under two-phase flow conditions | 33 |
| 7.2.1 | General | 33 |
| 7.2.2 | Identification of two-phase flow in the pipeline and well | 33 |
| 7.2.3 | State of the art of modelling two-phase CO2 flow in pipelines and wells | 34 |
| 7.2.4 | Shut-down and restart | 34 |
| 7.2.5 | Cavitation | 35 |
| 7.3 | Special operation with two-phase flow | 35 |
| 7.3.1 | Depressurization | 35 |
| 7.3.2 | Planned and un-planned pipeline pressure release | 36 |
| 7.3.3 | Well blowout | 37 |
| 7.3.4 | Leakage detection | 37 |
| 7.4 | Other issues | 37 |
| 7.4.1 | Dry ice formation | 37 |
| 7.4.2 | Hydrates | 37 |
| 7.5 | Ready for operation | 39 |
| 8 | Fluid flow in storage reservoirs | 40 |
| 8.1 | General | 40 |
| 8.2 | Depleted gas reservoirs | 42 |
| 8.3 | Saline aquifers | 44 |
| 8.4 | EOR operations | 45 |
| | Bibliography | 48 |