

ISO 5667-11:2009-04 (E)

Water quality - Sampling - Part 11: Guidance on sampling of groundwaters

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Sampling strategy and programme design | 4 |
| 4.1 | General | 4 |
| 4.2 | Selection of sampling point location | 4 |
| 4.3 | Groundwater parameter selection | 7 |
| 4.4 | Sampling frequency | 7 |
| 5 | Types of monitoring installation and sampling method | 8 |
| 5.1 | General | 8 |
| 5.2 | Unsaturated zone monitoring | 8 |
| 5.3 | Saturated zone | 11 |
| 6 | Sampling procedures | 15 |
| 6.1 | Purging | 15 |
| 6.2 | Trial pits | 19 |
| 6.3 | Sampling of free-phase contaminants (DNAPLs and LNAPLs) | 19 |
| 6.4 | Materials for sampling equipment | 19 |
| 6.5 | Prevention of contamination | 20 |
| 7 | Safety precautions | 21 |
| 8 | Sample identification and records | 22 |
| 9 | Quality assurance/quality control | 23 |
| Annex A (informative) Calculation of sampling frequency using nomogram | | 24 |
| Annex B (informative) Example of a report -- Sampling from groundwaters | | 25 |
| Bibliography | | 26 |