

ISO 18672-1:2009-06 (E)

Plastics piping systems for non-pressure drainage and sewerage - Polyester resin concrete (PRC) - Part 1: Pipes and fittings with flexible joints

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviations	2
3.1	Terms and definitions	2
3.2	Symbols and abbreviations	6
4	General requirements	9
4.1	Materials	9
4.2	Appearance	10
4.3	Reference conditions for testing	10
4.4	Joints	10
5	Pipes	11
5.1	Classification	11
5.2	Designation	12
5.3	Geometrical characteristics	12
5.4	Mechanical characteristics	20
5.5	Marking of pipes	24
6	Fittings	24
6.1	General	24
6.2	Bends	25
6.3	Branches	28
6.4	Marking of fittings	30
7	Joint performance	30
7.1	General	30
7.2	Requirements	30
Annex A (normative)	Test method for the determination of a pipe's crushing strength and ring bending tensile strength using a pipe test piece	34
Annex B (normative)	Test method for the determination of a pipe's crushing strength or ring bending tensile strength using test pieces sawn from a pipe	42
Annex C (normative)	Test methods for the assessment of longitudinal bending moment resistance	48
Annex D (normative)	Test method for the determination of the compressive strength of polyester resin concrete (PRC) using test pieces cut from a pipe	54
Annex E (normative)	Test method for the determination of the fatigue strength of a pipe under cyclic loading	58
Annex F (normative)	Method for the assessment of the leaktightness of a pipe and its joints under short-term exposure to internal water pressure	63
Annex G (normative)	Test method for the determination of the long-term (50 years) crushing strength of a pipe, including the effects of media attack	65