

DIN EN 14636-2:2010-04 (E)

Plastics piping systems for non-pressure drainage and sewerage - Polyester resin concrete (PR C) - Part 2: Manholes and inspection chambers

Contents		Page
Foreword		5
1	Scope	6
2	Normative references	6
3	Terms, definitions, symbols and abbreviations	7
3.1	Terms and definitions	7
3.2	Symbols and abbreviations	10
4	General requirements	12
4.1	Materials	12
4.1.1	General	12
4.1.2	Resin	12
4.1.3	Aggregates and fillers	13
4.1.4	Elastomers	13
4.1.5	Metals	13
4.1.6	Minimum resin content	13
4.2	Appearance	13
4.3	Reference conditions for testing	13
4.3.1	Temperature	13
4.3.2	Properties of water for testing	13
4.3.3	Loading conditions	13
4.3.4	Measurement of dimensions	13
4.4	Joints	14
4.4.1	General	14
4.4.2	Maximum angular deflection and/or maximum draw of flexible joints	14
4.4.3	Joint seals	14
4.4.4	Adhesives	14
5	Manholes and inspection chamber units	14
5.1	Classification	14
5.1.1	General	14
5.1.2	Intended use of structure	14
5.1.3	Type of unit	14
5.2	Designation	15
5.3	Geometrical characteristics	15
5.3.1	Chamber rings and shaft rings	15
5.3.2	Slabs and Tapers	17
5.3.3	Positioning of installed steps	18
5.3.4	Size of openings in manholes	19
5.3.5	Base units containing pipe connections	19
5.4	Mechanical characteristics	19
5.4.1	Crushing strength of chamber rings or shaft rings	19
5.4.2	Vertical crushing strength of slabs and tapers	21
5.4.3	Compressive strength of polyester resin concrete (PRC)	21
5.4.4	Leak-tightness of manholes and inspection chambers and their joints	21
5.4.5	Long-term crushing strength of chamber rings or shaft rings under media attack	22
5.4.6	Load bearing capacity of installed steps	22
5.5	Marking of manhole and inspection chamber units	22

6	Dangerous substances	23
7	Manufacturer's installation recommendations	23
8	Evaluation of conformity	23
8.1	General	23
8.2	Initial type testing	23
8.2.1	General	23
8.2.2	Characteristics	24
8.2.3	Use of historical data	24
8.2.4	"Deemed to satisfy" provisions and use of reference tabulated data	24
8.2.5	Treatment of calculated values and design	24
8.2.6	Sampling, testing and conformity criteria	25
8.3	Factory production control (FPC)	26
8.3.1	General	26
8.3.2	FPC requirements for all manufacturers	26
8.3.3	Manufacturer-specific FPC system requirements	27
8.4	One-off products, pre-production products (e.g. prototypes) and products produced in very low quantities	29
8.4.1	General	29
8.4.2	For initial type assessment	29
Annex A (normative) Determination of a chamber ring's or shaft ring's crushing strength and ring bending tensile strength using a ring test piece		30
A.1	Scope	30
A.2	Principle	30
A.3	Apparatus	30
A.4	Test pieces	32
A.5	Procedure	32
A.6	Calculations	32
A.7	Test report	35
Annex B (normative) Test method for the determination of a chamber ring's or shaft ring's crushing strength or the ring bending tensile strength using test pieces sawn from a ring		36
B.1	Scope	36
B.2	Principle	36
B.3	Apparatus	36
B.4	Test piece	37
B.5	Test procedure	38
B.6	Calculations	39
B.7	Test report	40
Annex C (normative) Test method for the determination of the vertical crushing strength of slabs or tapers		42
C.1	Scope	42
C.2	Principle	42
C.3	Apparatus	42
C.4	Preparation	42
C.5	Procedure	45
C.6	Test report	45
Annex D (normative) Test method for the determination of the compressive strength of polyester resin concrete (PRC) using test pieces which are cut from a unit		46
D.1	Scope	46
D.2	Principle	46
D.3	Apparatus	46
D.4	Test pieces	48

D.5	Procedure	49
D.6	Calculations	49
D.7	Test report	49
Annex E (normative) Test method for the determination of the resistance of installed steps to vertical and horizontal loading		50
E.1	Scope	50
E.2	Principle	50
E.3	Apparatus	50
E.4	Preparation	50
E.5	Procedure	51
E.6	Test report	51
Annex F (normative) Method for the assessment of the leak-tightness of a manhole or inspection chamber and its joints under short term exposure to internal water pressure and negative pressure		53
F.1	Scope	53
F.2	Principle	53
F.3	Apparatus	53
F.4	Test pieces	54
F.5	Procedure	54
F.6	Test report	54
Annex G (normative) Test method for the determination of the long-term crushing strength (50 years evaluation point) of a chamber ring or a shaft ring, including the effects of media attack		56
G.1	Scope	56
G.2	Principle	56
G.3	Apparatus	56
G.4	Test pieces	57
G.5	Test solutions	58
G.6	Procedure	58
G.7	Evaluation	59
G.8	Test report	59
Bibliography		60