ISO 1452-2:2009-12 (E)

Plastics piping systems for water supply and for bur ied and above-ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 2: Pipes

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviated terms 2

4 Material 3
4.1 Pipe material 3
4.2 Density 3
4.3 MRS-value 3

5 General characteristics 3
5.1 Appearance 3
5.2 Colour 3
5.3 Opacity of pipes intended for the above-ground conveyance of water 3

6 Geometrical characteristics 3
6.1 Measurement of dimensions 3
6.2 Nominal outside diameters 3
6.3 Mean outside diameters and their tolerances 4
6.4 Wall thickness and their tolerances 5
6.5 Length of pipe 6
6.6 Pipes with sockets 7
6.7 Pipe ends for ring seal or solvent cement joints 11

7 Classification and selection of pipes 11
7.1 Classification 11
7.2 Selection of nominal pressure and pipe series S for water up to and including 25 °C 11
7.3 Determination of the allowable operating pressure for water up to 45 °C 11

8 Mechanical characteristics 11
8.1 Impact strength 11
8.2 Resistance to internal pressure 12

9 Physical characteristics 13

10 Sealing rings 14
11 Adhesives 14
12 Performance requirements 14
13 Marking 14
13.1 General 14
13.2 Minimum required marking 14
13.3 Additional marking 15

Annex A (normative) Allowable operating pressures 16

Annex B (normative) Imperial (inch)-sized pipes 18

Bibliography 23