ISO 1452-3:2009-12 (E)

Plastics piping systems for water supply and for buried and above -ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 3: Fittings

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 2

3 Terms, definitions, symbols and abbreviated terms 3
3.1 Terms and definitions 3
3.2 Symbols 3

4 Material 3
4.1 Fitting material 3
4.2 Density 3
4.3 MRS-value 4

5 General characteristics 4
5.1 Appearance 4
5.2 Colour 4
5.3 Opacity of fittings intended for the above-ground conveyance of water 4

6 Geometrical characteristics 4
6.1 Measurement of dimensions 4
6.2 Nominal diameters 4
6.3 Fittings for solvent cementing 4
6.4 Adapter fittings 12
6.5 Tapping saddles 14
6.6 Flange adapters and flanges 17
6.7 Elastomeric ring seal fittings 20
6.8 End-load-bearing double-sockets with elastomeric seals 29

7 Classification and operating conditions 29
7.1 Classification 29
7.2 Selection of nominal pressure and pipe series S for water up to and including 25 °C 29
7.3 Determination of the allowable operating pressure for water up to 45 °C 30

8 Mechanical characteristics 30
8.1 Resistance to internal pressure of fittings or parts of fittings 30
8.2 Crushing test 31

9 Physical characteristics 31

10 Sealing rings 32

11 Adhesives 32

12 Performance requirements 32

13 Marking 32
13.1 General 32
13.2 Minimum required marking 32
13.3 Additional marking 33

Annex A (normative) Imperial(inch)-sized fittings 34

Bibliography 37