

ISO 11298-3:2010-03 (E)

Plastics piping systems for renovation of underground water supply networks - Part 3: Lining with close-fit pipes

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 3.1 | General | 2 |
| 3.2 | Techniques | 2 |
| 3.3 | Geometrics | 2 |
| 3.4 | Materials | 2 |
| 3.5 | Product stages | 2 |
| 3.6 | Service conditions | 2 |
| 3.7 | Joints | 3 |
| 4 | Symbols and abbreviated terms | 3 |
| 4.1 | Symbols | 3 |
| 4.2 | Abbreviated terms | 4 |
| 5 | Pipes at the "M" stage | 4 |
| 5.1 | Materials | 4 |
| 5.2 | General characteristics | 4 |
| 5.3 | Material characteristics | 4 |
| 5.4 | Geometric characteristics | 5 |
| 5.5 | Mechanical characteristics | 5 |
| 5.6 | Physical characteristics | 5 |
| 5.7 | Jointing | 5 |
| 5.8 | Marking | 5 |
| 6 | Fittings at the "M" stage | 5 |
| 7 | Ancillary components | 6 |
| 8 | Fitness for purpose of the installed lining system at the "I" stage | 6 |
| 8.1 | Materials | 6 |
| 8.2 | General characteristics | 6 |
| 8.3 | Material characteristics | 6 |
| 8.4 | Geometric characteristics | 6 |
| 8.5 | Mechanical characteristics | 7 |
| 8.6 | Physical characteristics | 8 |
| 8.7 | Additional characteristics | 8 |
| 8.8 | Sampling | 8 |
| 9 | Installation practice | 9 |
| 9.1 | Preparatory work | 9 |
| 9.2 | Storage, handling and transport | 9 |
| 9.3 | Equipment | 9 |
| 9.4 | Installation | 10 |
| 9.5 | Process-related inspection and testing | 11 |

| | |
|---|-----------|
| Annex A (normative) Factory-folded heat-reverted polyethylene (PE) pipe -- Determination of memory ability | 12 |
| Bibliography | 14 |