DIN EN 545:2011-09 (E)

Ductile iron pipes, fittings, accessories and their joints for water pipelines - Requirements and test methods

Contents

Page

Foreword 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 8

4 Technical requirements 12
4.1 General 12
4.2 Pressure class 13
4.3 Dimensional requirements 14
4.4 Material characteristics 18
4.5 Coatings and linings for pipes 19
4.6 Coatings for fittings and accessories 21
4.7 Marking of pipes, fittings and accessories 22
4.8 Leak tightness 23

5 Performance requirements for joints and pipe saddles 23
5.1 General 23
5.2 Flexible joints 23
5.3 Restrained flexible joints 25
5.4 Flanged joints as cast, screwed, welded and adjustable 25
5.5 Pipe saddles 26

6 Test methods 27
6.1 Pipe dimensions 27
6.2 Straightness of pipes 28
6.3 Tensile testing 28
6.4 Brinell hardness 30
6.5 Works leak tightness test for pipes and fittings 30
6.6 Zinc mass 30
6.7 Thickness of paint coatings 31
6.8 Thickness of cement mortar lining 31

7 Performance test methods 32
7.1 Compressive strength of the cement mortar lining 32
7.2 Leak tightness of flexible joints 32
7.3 Leak tightness and mechanical resistance of flanged joints 35
7.4 Leak tightness and mechanical resistance of pipe saddles 36

8 Tables of dimensions 37
8.1 Socket and spigot pipes 37
8.2 Flanged pipes 40
8.3 Fittings for socketed joints 40
8.4 Fittings for flanged joints 56

9 Evaluation of conformity 73
9.1 General 73
9.2 Initial performance testing 73
9.3 Factory production control (FPC) 75

Annex A (normative) Allowable pressures 80

A.1 General 80
A.2 Socket and spigot pipes (see 8.1) 80
A.3 Fittings for socketed joints (see 8.3) 80
A.4 Flanged pipes (see 8.2) and fittings for flanged joints (see 8.4) 81
A.5 Accessories 81

Annex B (informative) Longitudinal bending resistance of pipes 82

Annex C (informative) Diametral stiffness of pipes 83

Annex D (informative) Specific coatings, field of use, characteristics of soils 86

D.1 Alternative coatings 86
D.2 Field of use in relation to the characteristics of soils 87

Annex E (informative) Field of use, water characteristics 89

Annex F (informative) Calculation method of buried pipelines, heights of cover 90

F.1 Calculation method 90
F.2 Heights of cover 92

Bibliography 93

Tables Table 1 Limit deviations on thickness of fittings 14

Table 2 Limit deviation on internal diameter 15

Table 3 Maximum DN for limit deviations on internal diameter for pressure classes 15

Table 4 Standardized lengths of socket and spigot pipes 15

Table 5 Standardized lengths of flange pipes 16

Table 6 Permissible deviation on lengths of fittings 16

Table 7 Limit deviations on length 18

Table 8 Tensile properties 18

Table 9 Thickness of cement mortar lining 21

Table 10 DN groupings for performance tests 23

Table 11 Performance tests for joints 24

Table 12 Bending moments for flange joint performance tests 26

Table 13 Performance tests for pipe saddles 27

Table 14 Dimensions of test bar 29

Table 15 Works test pressure for pipes not centrifugally cast, fittings and accessories 30

Table 16 Dimensions of pipes of preferred pressure classes 38

Table 17 Dimensions of pipes 39

Table 18 Dimensions of flanged sockets 41

Table 19 Dimensions of flanged spigots and collars 43
Table 20 Dimensions of double socket 90° and 45° bends 45
Table 21 Dimensions of double socket 22,5º and 11,25º bends 47
Table 22 Dimensions of all socket tees 49
Table 23 Dimensions of double socket tees with flanged branch, DN 40 to 250 51
Table 24 Dimensions of double socket tees with flanged branch, DN 300 to DN 700 52
Table 25 Dimensions of double socket tees with flanged branch, DN 800 to DN 2 000 53
Table 26 Dimensions of double socket tapers 55
Table 27 Dimensions of double flanged 90º and 90º duckfoot bends 57
Table 28 Dimensions of double flanged 45° bends 59
Table 29 Dimensions of double flanged 22,5º and 11,25º bends 61
Table 30 Dimensions of all flanged tees, DN 40 to DN 250 62
Table 31 Dimensions of all flanged tees, DN 300 to DN 700 63
Table 32 Dimensions of all flanged tees, DN 800 to DN 2000 64
Table 33 Dimensions of double flanged tapers 66
Table 34 Dimensions of PN 10 and PN 16 blank flanges 68
Table 35 Dimensions of PN 25 and PN 40 blank flanges 70
Table 36 Dimensions of PN 10 and PN 16 reducing flanges 71
Table 37 Dimensions of PN 25 and PN 40 reducing flanges 73
Table 38 Number of test samples for initial performance testing 75
Table 39 Minimum frequency of product testing as part of FPC 77
Table 40 Maximum batch sizes for tensile testing 78
Table A.1 Fittings pressure class 81
Table A.2 Flanged pipe and fittings pressures 81
Table B.1 Longitudinal bending moment resistance of pipes 82
Table C.1 Diametral stiffness of pipes of preferred pressure classes 85
Table E.1 Field of use for cement mortar linings 89
Table F.1 Heights of cover for pipes of preferred pressure classes 92
Figures Figure 1 Leak tightness test of joints (internal pressure) 33
Figure 2 Leak tightness test of joints (external pressure) 34
Figure 3 Strength and leak tightness test for flanged joints 35

Figure 4 Leak tightness test for pipe saddles 36

Figure 5 Socket and spigot pipes 37

Figure 6 Flanged sockets 40

Figure 7 Flanged spigots 42

Figure 8 Collars 42

Figure 9 Double socket 90° (1/4) bends 44

Figure 10 Double socket 45° (1/8) bends 44

Figure 11 Double socket 22°30' (1/16) bends 46

Figure 12 Double socket 11°15' (1/32) bends 46

Figure 13 All socket tees 48

Figure 14 Double socket tees with flanged branch 50

Figure 15 Double socket tapers 54

Figure 16 Double flanged 90° (1/4) bends 56

Figure 17 Double flanged duckfoot 90° (1/4) bends 57

Figure 18 Double flanged 45° (1/8) bends 58

Figure 19 Double flanged 22°30' (1/16) bends 60

Figure 20 Double flanged 11°15' (1/32) bends 60

Figure 21 All flanged tees 61

Figure 22 Double flanged tapers 65

Figure 23 Blank flanges PN 10 67

Figure 24 Blank flanges PN 16 67

Figure 25 Blank flanges PN 25 69

Figure 26 Blank flanges PN 40 69

Figure 27 Reducing flanges PN 10 70

Figure 28 Reducing flanges PN 16 71

Figure 29 Reducing flanges PN 25 72

Figure 30 Reducing flanges PN 40 72