ISO 11296-7:2011-11 (E)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 7: Lining with spirally-wound pipes

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and abbreviated terms 3
4.1 Symbols 3
4.2 Abbreviated terms 3

5 Pipes at the "M" stage 3
5.1 Materials 3
5.2 General characteristics 4
5.3 Material characteristics 4
5.4 Geometric characteristics 5
5.5 Mechanical characteristics 6
5.6 Physical characteristics 6
5.7 Jointing 6
5.8 Marking 6

6 Fittings at the "M" stage 7

7 Ancillary components 7

8 Fitness for purpose of the installed lining system at the "I" stage 7
8.1 Materials 7
8.2 General characteristics 7
8.3 Material characteristics 7
8.4 Geometric characteristics 7
8.5 Mechanical characteristics 7
8.6 Physical characteristics 8
8.7 Additional characteristics 8
8.8 Preparation of samples 8
8.9 Adhesives 8

9 Installation practice 8
9.1 Preparatory work 8
9.2 Storage, handling and transportation of profiled plastics strips and fittings 8
9.3 Equipment 8
9.4 Installation 9
9.5 Processrelated inspection and testing 10
9.6 Lining termination 10
9.7 Reconnecting to existing manholes and laterals 10
9.8 Final inspection and testing 10
9.9 Documentation 10

Annex A (normative) Spirallywound pipe -- Test method for watertightness in a deflected condition 11

Annex B (informative) Examples of methods for reconnecting and sealing laterals to SWO pipe 14

Bibliography 16