

ISO 11296-7:2011-11 (E)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 7: Lining with spirally-wound pipes

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	3
4.1	Symbols	3
4.2	Abbreviated terms	3
5	Pipes at the "M" stage	3
5.1	Materials	3
5.2	General characteristics	4
5.3	Material characteristics	4
5.4	Geometric characteristics	5
5.5	Mechanical characteristics	6
5.6	Physical characteristics	6
5.7	Jointing	6
5.8	Marking	6
6	Fittings at the "M" stage	7
7	Ancillary components	7
8	Fitness for purpose of the installed lining system at the "I" stage	7
8.1	Materials	7
8.2	General characteristics	7
8.3	Material characteristics	7
8.4	Geometric characteristics	7
8.5	Mechanical characteristics	7
8.6	Physical characteristics	8
8.7	Additional characteristics	8
8.8	Preparation of samples	8
8.9	Adhesives	8
9	Installation practice	8
9.1	Preparatory work	8
9.2	Storage, handling and transportation of profiled plastics strips and fittings	8
9.3	Equipment	8
9.4	Installation	9
9.5	Processrelated inspection and testing	10
9.6	Lining termination	10
9.7	Reconnecting to existing manholes and laterals	10
9.8	Final inspection and testing	10
9.9	Documentation	10

Annex A (normative) Spirallywound pipe -- Test method for watertightness in a deflected condition	11
Annex B (informative) Examples of methods for reconnecting and sealing laterals to SWO pipe	14
Bibliography	16