

DIN EN 15934:2012-11 (E)

Sludge, treated biowaste, soil and waste - Calculation of dry matter fraction after determination of dry residue or water content

Contents		Page
Foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Principle	5
4.1	General	5
4.2	Principle of Method A -- Drying at 105 °C (dry residue)	6
4.3	Principle of Method B -- Direct Karl-Fischer-titration (water content)	6
5	Sample preparation	6
6	Method A -- Drying at 105 °C	6
6.1	General	6
6.2	Interferences	6
6.3	Hazards	6
6.4	Apparatus	6
6.5	Procedure	7
6.6	Calculation of results	7
7	Method B -- Direct Karl-Fischer-titration (volumetric/coulometric detection)	8
7.1	Interferences	8
7.2	Reagents	8
7.3	Apparatus	8
7.4	Procedure	8
7.4.1	Determination of the equivalence factor	8
7.4.2	Analysis of liquid samples	9
7.4.3	Analysis of solid samples	9
8	Calculation of dry matter fraction	10
9	Precision	10
10	Test report	10
Annex A (informative) Repeatability and reproducibility		11
A.1	Performance characteristics	11
A.2	Types of samples and sample preparation	12
A.3	Homogeneity and stability	13
A.4	Dry matter fraction results by different methods	14
Annex B (informative) Azeotropic distillation with toluene		15
B.1	General	15
B.2	Interferences	15

B.3	Hazards	15
B.4	Reagents	15
B.5	Apparatus	15
B.6	Procedure	16
B.7	Calculation of results	16
B.8	System performance check	16
B.9	Performance data	17
Annex C (informative) Summary of general requirements and recommendations		19