

DIN 1988-300:2012-05 (E)

Codes of practice for drinking water installations - Part 300: Pipe sizing; DVGW code of practice

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms, symbols and units | 6 |
| 4 | Sizing principles | 11 |
| 4.1 | General | 11 |
| 4.2 | Pipe friction | 11 |
| 4.3 | Individual head losses | 13 |
| 5 | Sizing of cold and hot water pipes | 14 |
| 5.1 | General | 14 |
| 5.2 | Design and total flow rates | 14 |
| 5.2.1 | Design flow rate | 14 |
| 5.2.2 | Determining the total flow rate | 17 |
| 5.3 | Determining the peak flow rate | 18 |
| 5.4 | Determining the available friction loss | 20 |
| 5.4.1 | General | 20 |
| 5.4.2 | Percentage head loss due to individual head losses a | 20 |
| 5.4.3 | Total pipe length lges | 21 |
| 5.4.4 | Minimum supply pressure | 21 |
| 5.4.5 | Head loss due to difference in elevation pgeo | 21 |
| 5.4.6 | Sum of head losses in appliances | 21 |
| 5.5 | Pipe sizing for the hydraulically most unfavourable flow path | 23 |
| 5.6 | Flow balancing to obtain the hydraulically more favourable flow path | 24 |
| 5.7 | Special considerations concerning circulation main branch pipe of usage units | 24 |
| 6 | Design of circulation systems | 24 |
| 6.1 | General | 24 |
| 6.2 | Downfeed systems | 25 |
| 6.2.1 | Heat losses and flow rates | 25 |
| 6.2.2 | Diameter of circulation pipes and pump pressure | 27 |
| 6.3 | Upfeed systems | 28 |
| 6.4 | Smart loop systems | 29 |
| 6.5 | Balancing the system | 29 |
| 7 | Documentation | 29 |
| 7.1 | General | 29 |
| 7.2 | Hot and cold water pipes | 29 |
| 7.3 | Circulation systems | 30 |
| Annex A (informative) | Comparable pipe nominal sizes and resistance coefficients for fittings and valves of dissimilar materials | 32 |
| Annex B (informative) | Presentation of design assumptions | 43 |
| Bibliography | | 44 |