

# DIN EN 15383:2013-03 (E)

## Plastics piping systems for drainage and sewerage - Glass-reinforced thermosetting plastics (GRP) based on polyester resin (UP) - Manholes and inspection chambers

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>6</b>
<b>4</b>	<b>General requirements .....</b>	<b>12</b>
<b>4.1</b>	<b>Classification .....</b>	<b>12</b>
<b>4.1.1</b>	<b>Categories .....</b>	<b>12</b>
<b>4.1.2</b>	<b>Nominal stiffness .....</b>	<b>12</b>
<b>4.2</b>	<b>Materials for shaft or chamber units .....</b>	<b>12</b>
<b>4.2.1</b>	<b>General .....</b>	<b>12</b>
<b>4.2.2</b>	<b>Elastomers .....</b>	<b>12</b>
<b>4.2.3</b>	<b>Metals .....</b>	<b>12</b>
<b>4.3</b>	<b>Reference conditions for testing .....</b>	<b>13</b>
<b>4.3.1</b>	<b>Temperature .....</b>	<b>13</b>
<b>4.3.2</b>	<b>Properties of water for testing .....</b>	<b>13</b>
<b>4.3.3</b>	<b>Loading conditions .....</b>	<b>13</b>
<b>4.3.4</b>	<b>Preconditioning .....</b>	<b>13</b>
<b>4.3.5</b>	<b>Measurement of dimensions .....</b>	<b>13</b>
<b>4.4</b>	<b>Joints .....</b>	<b>13</b>
<b>4.4.1</b>	<b>Types of joint .....</b>	<b>13</b>
<b>4.4.2</b>	<b>Length and diameter of joint .....</b>	<b>13</b>
<b>4.4.3</b>	<b>Flexibility of the jointing system .....</b>	<b>13</b>
<b>4.4.4</b>	<b>Sealing ring .....</b>	<b>13</b>
<b>4.4.5</b>	<b>Adhesives .....</b>	<b>13</b>
<b>4.5</b>	<b>Joint performance .....</b>	<b>14</b>
<b>4.5.1</b>	<b>Performance requirements .....</b>	<b>14</b>
<b>4.5.2</b>	<b>Interchangeability .....</b>	<b>14</b>
<b>4.5.3</b>	<b>Test pieces .....</b>	<b>15</b>
<b>4.5.4</b>	<b>Number of test pieces for type test purposes .....</b>	<b>15</b>
<b>4.5.5</b>	<b>Test temperature .....</b>	<b>15</b>
<b>4.5.6</b>	<b>Flexible joints with elastomeric sealing rings .....</b>	<b>15</b>
<b>4.5.7</b>	<b>Rigid joints of the wrapped or cemented type .....</b>	<b>15</b>
<b>4.5.8</b>	<b>Test parameters .....</b>	<b>15</b>
<b>5</b>	<b>Geometrical characteristics .....</b>	<b>16</b>
<b>5.1</b>	<b>Diameter, wall thickness and length of GRP-UP shaft and chamber components</b> <b>Dimensional requirement .....</b>	<b>16</b>
<b>5.2</b>	<b>Size of openings in manholes .....</b>	<b>16</b>
<b>6</b>	<b>Mechanical characteristics .....</b>	<b>16</b>
<b>6.1</b>	<b>General .....</b>	<b>16</b>
<b>6.2</b>	<b>Longitudinal compressive strength .....</b>	<b>16</b>
<b>6.2.1</b>	<b>Initial longitudinal compressive stress at break .....</b>	<b>16</b>
<b>6.2.2</b>	<b>Requirements .....</b>	<b>16</b>
<b>6.3</b>	<b>Longitudinal compressive load .....</b>	<b>17</b>
<b>6.3.1</b>	<b>General .....</b>	<b>17</b>
<b>6.3.2</b>	<b>Ultimate longitudinal load, Fult .....</b>	<b>17</b>

6.3.3	Manufacturer's declared load for which a manhole or inspection chamber ring is designed, $F_j$ and the permissible force, $F_{perm}$ , p .....	17
7	Leak-tightness of manholes and inspection chambers and their joints .....	18
8	Minimum required marking .....	18
9	Ancillary products .....	19
9.1	Manhole and inspection chamber tops .....	19
9.2	Manhole steps and ladders .....	19
9.2.1	Location of steps .....	19
9.2.2	Load bearing capacity of installed steps .....	20
9.3	Precast concrete components .....	21
10	Dangerous substances .....	21
11	Manufacturer's installation recommendations .....	21
12	Evaluation of conformity .....	21
<b>Annex A (normative) Determination of the longitudinal compressive properties measured on prism shaped test pieces .....</b>		
		<b>22</b>
A.1	Scope .....	22
A.2	General .....	22
A.3	Test-pieces .....	22
A.4	Test equipment .....	25
A.5	Test procedure .....	25
A.6	Calculation and expression of results .....	25
A.7	Test report .....	26
<b>Annex B (normative) Determination of the resistance of installed steps to vertical or horizontal loading</b>		
27 B.1	Scope .....	27
B.2	Principle .....	27
B.3	Apparatus .....	27
B.4	Preparation .....	27
B.5	Procedure .....	28
B.6	Test report .....	29